

NAME

autoupdate - Update a configure.in to a newer Autoconf

SYNOPSIS

autoupdate [*OPTION*]... [*TEMPLATE-FILE*]...

DESCRIPTION

Update each *TEMPLATE-FILE* if given, or ‘configure.ac’ if present, or else ‘configure.in’, to the syntax of the current version of Autoconf. The original files are backed up.

Operation modes:

- h, --help**
print this help, then exit
- V, --version**
print version number, then exit
- v, --verbose**
verbosely report processing
- d, --debug**
don't remove temporary files
- f, --force**
consider all files obsolete

Library directories:

- B, --prepend-include=DIR**
prepend directory *DIR* to search path
- I, --include=DIR**
append directory *DIR* to search path

AUTHOR

Written by David J. MacKenzie and Akim Demaille.

REPORTING BUGS

Report bugs to <bug-autoconf@gnu.org>.
GNU Autoconf home page: <<http://www.gnu.org/software/autoconf/>>.
General help using GNU software: <<http://www.gnu.org/gethelp/>>.

COPYRIGHT

Copyright 2012 Free Software Foundation, Inc. License GPLv3+/Autoconf: GNU GPL version 3 or later <<http://gnu.org/licenses/gpl.html>>, <<http://gnu.org/licenses/exceptions.html>>
This is free software: you are free to change and redistribute it. There is NO WARRANTY, to the extent permitted by law.

SEE ALSO

[autoconf\(1\)](#), [automake\(1\)](#), [autoreconf\(1\)](#), [autoupdate\(1\)](#), [autoheader\(1\)](#), [autoscan\(1\)](#), [config.guess\(1\)](#), [config.sub\(1\)](#), [ifnames\(1\)](#), [libtool\(1\)](#).

The full documentation for **autoupdate** is maintained as a Texinfo manual. If the **info** and **autoupdate** programs are properly installed at your site, the command

info autoupdate

should give you access to the complete manual.