

**NAME**

autoupdate - Update a configure.in to a newer Autoconf

**SYNOPSIS**

**autoupdate** [*OPTION*]... [*TEMPLATE-FILE*]...

**DESCRIPTION**

Update each *TEMPLATE-FILE* if given, or 'configure.ac' if present, or else 'configure.in', to the syntax of the current version of Autoconf. The original files are backed up.

**Operation modes:****-h, --help**

print this help, then exit

**-V, --version**

print version number, then exit

**-v, --verbose**

verbosely report processing

**-d, --debug**

don't remove temporary files

**-f, --force**

consider all files obsolete

**Library directories:****-B, --prepend-include=DIR**

prepend directory *DIR* to search path

**-I, --include=DIR**

append directory *DIR* to search path

**AUTHOR**

Written by David J. MacKenzie and Akim Demaille.

**REPORTING BUGS**

Report bugs to <[bug-autoconf@gnu.org](mailto:bug-autoconf@gnu.org)>.

GNU Autoconf home page: <<http://www.gnu.org/software/autoconf/>>.

General help using GNU software: <<http://www.gnu.org/gethelp/>>.

**COPYRIGHT**

Copyright © 2012 Free Software Foundation, Inc. License GPLv3+/Autoconf: GNU GPL version 3 or later <<http://gnu.org/licenses/gpl.html>>, <<http://gnu.org/licenses/exceptions.html>>

This is free software: you are free to change and redistribute it. There is NO WARRANTY, to the extent permitted by law.

**SEE ALSO**

[autoconf\(1\)](#), [automake\(1\)](#), [autoreconf\(1\)](#), [autoupdate\(1\)](#), [autoheader\(1\)](#), [autoscan\(1\)](#), [config.guess\(1\)](#), [config.sub\(1\)](#), [ifnames\(1\)](#), [libtool\(1\)](#).

The full documentation for **autoupdate** is maintained as a Texinfo manual. If the **info** and **autoupdate** programs are properly installed at your site, the command

**info autoupdate**

should give you access to the complete manual.