

NAME

colcrt — filter nroff output for CRT previewing

SYNOPSIS

colcrt [-] [-2] [*file* . . .]

DESCRIPTION

The **colcrt** utility provides virtual half-line and reverse line feed sequences for terminals without such capability, and on which overstriking is destructive. Half-line characters and underlining (changed to dash-ing ‘-’) are placed on new lines in between the normal output lines.

The following options are available:

- Suppress all underlining. This option is especially useful for previewing *allboxed* tables from [tbl\(1\)](#).
- 2 Cause all half-lines to be printed, effectively double spacing the output. Normally, a minimal space output format is used which will suppress empty lines. The program never suppresses two consecutive empty lines, however. The -2 option is useful for sending output to the line printer when the output contains superscripts and subscripts which would otherwise be invisible.

ENVIRONMENT

The LANG, LC_ALL and LC_CTYPE environment variables affect the execution of **colcrt** as described in [environ\(7\)](#).

EXIT STATUS

The **colcrt** utility exits 0 on success, and >0 if an error occurs.

EXAMPLES

A typical use of **colcrt** would be

```
tbl exum2.n | nroff -ms | colcrt - | more
```

SEE ALSO

[col\(1\)](#), [more\(1\)](#), [nroff\(1\)](#), [troff\(1\)](#), [ul\(1\)](#)

HISTORY

The **colcrt** command appeared in 3.0BSD.

BUGS

Should fold underlines onto blanks even with the ‘-’ option so that a true underline character would show.

Cannot back up more than 102 lines.

General overstriking is lost; as a special case ‘|’ overstruck with ‘-’ or underline becomes ‘+’.

Lines are trimmed to 132 characters.

Some provision should be made for processing superscripts and subscripts in documents which are already double-spaced.

Characters that take up more than one column position may not be underlined correctly.