

NAME

env - run a program in a modified environment

SYNOPSIS

env [*OPTION*]... [-] [*NAME=VALUE*]... [*COMMAND* [*ARG*]...]

DESCRIPTION

Set each *NAME* to *VALUE* in the environment and run *COMMAND*.

Mandatory arguments to long options are mandatory for short options too.

-i, --ignore-environment

start with an empty environment

-0, --null

end each output line with NUL, not newline

-u, --unset=*NAME*

remove variable from the environment

--help display this help and exit

--version

output version information and exit

A mere - implies **-i**. If no *COMMAND*, print the resulting environment.

AUTHOR

Written by Richard Mlynarik and David MacKenzie.

REPORTING BUGS

GNU coreutils online help: <<http://www.gnu.org/software/coreutils/>>

Report env translation bugs to <<http://translationproject.org/team/>>

COPYRIGHT

Copyright 2014 Free Software Foundation, Inc. License GPLv3+: GNU GPL version 3 or later <<http://gnu.org/licenses/gpl.html>>.

This is free software: you are free to change and redistribute it. There is NO WARRANTY, to the extent permitted by law.

SEE ALSO

Full documentation at: <<http://www.gnu.org/software/coreutils/env>>

or available locally via: info (coreutils) env invocation