

NAME

faked - daemon that remembers fake ownership/permissions of files manipulated by fakeroot processes.

SYNOPSIS

faked [**--debug**] [**--foreground**] [**--cleanup**] [**--key** *msg-key*] [**--load**] [**--save-file** *save-file*] [**--port** *TCP-port*]

DESCRIPTION

If a fakeroot process wants to change the ownership of a file, then **faked** is the process that remembers that new owner. If later the same fakeroot process does a `stat()` for that filename, then the libfakeroot wrapped `stat()` call will first ask faked for the fake ownership etc of that file, and then report it.

OPTIONS

--debug

Print debugging information on stderr.

--foreground

Don't fork into the background.

--cleanup **number**

Cleanup the semaphores.

--key **key-number**

Don't allocate a new communication channel, but use channel specified by key. (If the specified channel doesn't exist, it's created).

--save-file **save-file**

Save the environment to save-file on exit.

--load Load a previously saved environment from the standard input.

--unknown-is-real

Use real ownership of previously-unknown files instead of setting them to root:root.

--port **tcp-port**

Use TCP port tcp-port.

BUGS

None so far. Be warned, though: although I've written quite a few much larger (and smaller) programs, I've never written anything that was as tiny as **fakeroot**, had as many bugs as **fakeroot**, and still was as usable as, say, **fakeroot** version 0.0_3, the first version that could be used to build itself.

COPYING

fakeroot is distributed under the GNU General Public License. (GPL 2.0 or greater).

AUTHORS

joost witteveen

<joostje@debian.org>

Clint Adams

<clint@debian.org>

Timo Savola

MANUAL PAGE

mostly by J.H.M. Dassen <jdassen@debian.org> mods/additions by joost and Clint.

SEE ALSO

[fakeroot\(1\)](#), [dpkg-buildpackage\(1\)](#), [debbuild\(1\)](#) /usr/share/doc/fakeroot/DEBUG