

NAME

TOilet - display large colourful characters

SYNOPSIS

```
toilet [ -hkostvSW ] [ -d fontdirectory ]
        [ -f fontfile ] [ -F filter ] [ -w outputwidth ]
        [ -I infocode ] [ -E format ] [ message ]
```

DESCRIPTION

TOilet prints text using large characters made of smaller characters. It is similar in many ways to **FIGlet** with additional features such as Unicode handling, colour fonts, filters and various export formats.

USAGE

TOilet either reads its input from the command line or from the standard input.

OPTIONS**-f, --font <name>**

Use the given font instead of the default value. Fonts are **.ff** or **.tlf** files stored in the **/usr/share/figlet** directory. Fonts are looked first in the font directory, then in the current directory. There is also a special built-in font called *term* that serves as a fallback if no font is available.

-d, --directory <dir>

Specify the directory in which to look for fonts. The default value is set at build time and usually defaults to **/usr/share/figlet**.

-s, -S, -k, -W, -o

Select character composition rules. **-S** sets sm ushing (nicely merging glyphs), **-k** sets kerning (rendering subcharacters as close to each other as possible), **-W** renders characters at their full width and **-o** sets overlapping (glyphs slightly overlap the previous one). **-s** (default behaviour) uses the font's smushing information if any, otherwise forces overlapping, or does nothing if the glyph only has one subcharacter.

-w, --width <width>

Set the output width. By default, **TOilet** will wrap its output at 80 character columns.

-t, --termwidth

Set the output width to the terminal width.

-F, --filter <filters>**-F, --filter list****--gay, --metal**

Specify a list of filters to be applied to the output. *<filters>* is a colon-separated list of filters such as *crop:rotate:gay* and the special argument *list* outputs a list of available filters.

--gay and **--metal** are shortcuts to commonly used filters that are guaranteed to exist. Several **-F** flags can also be specified on the command line, in which case filters will be applied in order of appearance.

-E, --export <format>**-E, --export list****--irc, --html**

Specify the output format. By default, **TOilet** will output UTF-8 text using ANSI colour codes suitable for most terminals such as XTerm or rxvt. *<format>* is the name of the export format as recognised by libcasa. The special argument *list* outputs a list of available export formats.

--irc and **--html** are shortcuts to commonly used export formats that are guaranteed to exist.

-h, --help

Display a short help message and exit.

-I, --infocode <code>

Print a **FIGlet** infocode. This flag is only here for **FIGlet** compatibility, see the **figlet** manpage for more information about it.

-v, --version

Output version information and exit.

EXAMPLES

```
toilet Hello World
```

```
toilet Hello | toilet
```

```
tail -f /var/log/messages | toilet -f term --gay
```

BUGS

FIGlet compatibility is not complete yet.

AUTHOR

TOilet and this manual page were written by Sam Hocevar <sam@hocevar.net>. There is a webpage available at <http://caca.zoy.org/wiki/toilet>

SEE ALSO

[figlet\(6\)](#)