

NAME

git-instaweb - Instantly browse your working repository in gitweb

SYNOPSIS

```
git instaweb [--local] [--httpd=<httpd>] [--port=<port>]
[--browser=<browser>]
git instaweb[--start] [--stop] [--restart]
```

DESCRIPTION

A simple script to set up gitweb and a web server for browsing the local repository.

OPTIONS

-l, --local

Only bind the web server to the local IP (127.0.0.1).

-d, --httpd

The HTTP daemon command-line that will be executed. Command-line options may be specified here, and the configuration file will be added at the end of the command-line. Currently apache2, lighttpd, mongoose, plackup and webrick are supported. (Default: lighttpd)

-m, --module-path

The module path (only needed if httpd is Apache). (Default: /usr/lib/apache2/modules)

-p, --port

The port number to bind the httpd to. (Default: 1234)

-b, --browser

The web browser that should be used to view the gitweb page. This will be passed to the *git web--browse* helper script along with the URL of the gitweb instance. See [git-web--browse\(1\)](#) for more information about this. If the script fails, the URL will be printed to stdout.

start, --start

Start the httpd instance and exit. Regenerate configuration files as necessary for spawning a new instance.

stop, --stop

Stop the httpd instance and exit. This does not generate any of the configuration files for spawning a new instance, nor does it close the browser.

restart, --restart

Restart the httpd instance and exit. Regenerate configuration files as necessary for spawning a new instance.

CONFIGURATION

You may specify configuration in your `.git/config`

```
[instaweb]
local = true
httpd = apache2 -f
port = 4321
browser = konqueror
modulepath = /usr/lib/apache2/modules
```

If the configuration variable `instaweb.browser` is not set, `web.browser` will be used instead if it is defined. See [git-web--browse\(1\)](#) for more information about this.

SEE ALSO

[gitweb\(1\)](#)

GIT

Part of the [git\(1\)](#) suite