

NAME

git-prune - Prune all unreachable objects from the object database

SYNOPSIS

```
git prune [-n] [-v] [--expire <expire>] [--] [<head>...]
```

DESCRIPTION**Note**

In most cases, users should run *git gc*, which calls *git prune*. See the section NOTES, below.

This runs *git fsck --unreachable* using all the refs available in refs/, optionally with additional set of objects specified on the command line, and prunes all unpacked objects unreachable from any of these head objects from the object database. In addition, it prunes the unpacked objects that are also found in packs by running *git prune-packed*. It also removes entries from .git/shallow that are not reachable by any ref.

Note that unreachable, packed objects will remain. If this is not desired, see [git-repack\(1\)](#).

OPTIONS

-n, --dry-run

Do not remove anything; just report what it would remove.

-v, --verbose

Report all removed objects.

--

Do not interpret any more arguments as options.

--expire <time>

Only expire loose objects older than <time>.

<head>...

In addition to objects reachable from any of our references, keep objects reachable from listed <head>s.

EXAMPLE

To prune objects not used by your repository or another that borrows from your repository via its .git/objects/info/alternates:

```
$ git prune $(cd ../another && git rev-parse --all)
```

NOTES

In most cases, users will not need to call *git prune* directly, but should instead call *git gc*, which handles pruning along with many other housekeeping tasks.

For a description of which objects are considered for pruning, see *git fscks --unreachable* option.

SEE ALSO

[git-fsck\(1\)](#), [git-gc\(1\)](#), [git-reflog\(1\)](#)

GIT

Part of the [git\(1\)](#) suite