

NAME

head - output the first part of files

SYNOPSIS

head [*OPTION*]... [*FILE*]...

DESCRIPTION

Print the first 10 lines of each *FILE* to standard output. With more than one *FILE*, precede each with a header giving the file name. With no *FILE*, or when *FILE* is -, read standard input.

Mandatory arguments to long options are mandatory for short options too.

-c, --bytes=[-]*K*

print the first *K* bytes of each file; with the leading '-', print all but the last *K* bytes of each file

-n, --lines=[-]*K*

print the first *K* lines instead of the first 10; with the leading '-', print all but the last *K* lines of each file

-q, --quiet, --silent

never print headers giving file names

-v, --verbose

always print headers giving file names

--help display this help and exit

--version

output version information and exit

K may have a multiplier suffix: b 512, kB 1000, K 1024, MB 1000*1000, M 1024*1024, GB 1000*1000*1000, G 1024*1024*1024, and so on for T, P, E, Z, Y.

AUTHOR

Written by David MacKenzie and Jim Meyering.

REPORTING BUGS

GNU coreutils online help: <<http://www.gnu.org/software/coreutils/>>

Report head translation bugs to <<http://translationproject.org/team/>>

COPYRIGHT

Copyright 2014 Free Software Foundation, Inc. License GPLv3+: GNU GPL version 3 or later <<http://gnu.org/licenses/gpl.html>>.

This is free software: you are free to change and redistribute it. There is NO WARRANTY, to the extent permitted by law.

SEE ALSO

Full documentation at: <<http://www.gnu.org/software/coreutils/head>>

or available locally via: info (coreutils) head invocation