

NAME

m4 - macro processor

SYNOPSIS

m4 [*OPTION*]... [*FILE*]...

DESCRIPTION

Process macros in *FILE*s. If no *FILE* or if *FILE* is '-', standard input is read.

Mandatory or optional arguments to long options are mandatory or optional for short options too.

Operation modes:

- help** display this help and exit
- version**
output version information and exit
- E, --fatal-warnings**
once: warnings become errors, twice: stop execution at first error
- i, --interactive**
unbuffer output, ignore interrupts
- P, --prefix-builtins**
force a 'm4_' prefix to all builtins
- Q, --quiet, --silent**
suppress some warnings for builtins
- warn-macro-sequence**[=*REGEXP*]
warn if macro definition matches *REGEXP*,
default $\$({[^\}]*}[0-9][0-9]+)$

Preprocessor features:

- D, --define=NAME**[=*VALUE*]
define *NAME* as having *VALUE*, or empty
- I, --include=DIRECTORY**
append *DIRECTORY* to include path
- s, --synclines**
generate '#line NUM FILE' lines
- U, --undefine=NAME**
undefine *NAME*

Limits control:

- g, --gnu**
override **-G** to re-enable GNU extensions
- G, --traditional**
suppress all GNU extensions
- H, --hashsize=PRIME**
set symbol lookup hash table size [509]
- L, --nesting-limit=NUMBER**
change nesting limit, 0 for unlimited [0]

Frozen state files:

- F, --freeze-state=FILE**
produce a frozen state on *FILE* at end
- R, --reload-state=FILE**
reload a frozen state from *FILE* at start

Debugging:

- d, --debug**[=*FLAGS*]
set debug level (no *FLAGS* implies ‘aeq’)
- debugfile**[=*FILE*]
redirect debug and trace output to *FILE* (default stderr, discard if empty string)
- l, --arglength**=*NUM*
restrict macro tracing size
- t, --trace**=*NAME*
trace *NAME* when it is defined

FLAGS is any of:

- a show actual arguments
- c show before collect, after collect and after call
- e show expansion
- f say current input file name
- i show changes in input files
- l say current input line number
- p show results of path searches
- q quote values as necessary, with a or e flag
- t trace for all macro calls, not only traceon’ed
- x add a unique macro call id, useful with c flag
- V shorthand for all of the above flags

If defined, the environment variable ‘M4PATH’ is a colon-separated list of directories included after any specified by ‘-I’.

Exit status is 0 for success, 1 for failure, 63 for frozen file version mismatch, or whatever value was passed to the `m4exit` macro.

AUTHOR

Written by Rene’ Seindal.

REPORTING BUGS

Report bugs to: bug-m4@gnu.org

GNU M4 home page: <<http://www.gnu.org/software/m4/>>

General help using GNU software: <<http://www.gnu.org/gethelp/>>

COPYRIGHT

Copyright 2013 Free Software Foundation, Inc. License GPLv3+: GNU GPL version 3 or later <<http://gnu.org/licenses/gpl.html>>.

This is free software: you are free to change and redistribute it. There is NO WARRANTY, to the extent permitted by law.

SEE ALSO

The full documentation for **m4** is maintained as a Texinfo manual. If the **info** and **m4** programs are properly installed at your site, the command

info m4

should give you access to the complete manual.