

NAME

locate - find files by name

SYNOPSIS

locate [*OPTION*]... *PATTERN*...

DESCRIPTION

locate reads one or more databases prepared by [updatedb\(8\)](#) and writes file names matching at least one of the *PATTERNS* to standard output, one per line.

If **--regex** is not specified, *PATTERNS* can contain globbing characters. If any *PATTERN* contains no globbing characters, **locate** behaves as if the pattern were **PATTERN**.

By default, **locate** does not check whether files found in database still exist (but it does require all parent directories to exist if the database was built with **--require-visibility no**). **locate** can never report files created after the most recent update of the relevant database.

EXIT STATUS

locate exits with status 0 if any match was found or if **locate** was invoked with one of the **--limit 0**, **--help**, **--statistics** or **--version** options. If no match was found or a fatal error was encountered, **locate** exits with status 1.

Errors encountered while reading a database are not fatal, search continues in other specified databases, if any.

OPTIONS

-A, --all

Print only entries that match all *PATTERNS* instead of requiring only one of them to match.

-b, --basename

Match only the base name against the specified patterns. This is the opposite of **--wholename**.

-c, --count

Instead of writing file names on standard output, write the number of matching entries only.

-d, --database*DBPATH*

Replace the default database with *DBPATH*. *DBPATH* is a **:**-separated list of database file names. If more than one **--database** option is specified, the resulting path is a concatenation of the separate paths.

An empty database file name is replaced by the default database. A database file name **-** refers to the standard input. Note that a database can be read from the standard input only once.

-e, --existing

Print only entries that refer to files existing at the time **locate** is run.

-L, --follow

When checking whether files exist (if the **--existing** option is specified), follow trailing symbolic links. This causes broken symbolic links to be omitted from the output.

This is the default behavior. The opposite can be specified using **--nofollow**.

-h, --help

Write a summary of the available options to standard output and exit successfully.

-i, --ignore-case

Ignore case distinctions when matching patterns.

-l, --limit, -n *LIMIT*

Exit successfully after finding *LIMIT* entries. If the **--count** option is specified, the resulting count is also limited to *LIMIT*.

-m, --mmap

Ignored, for compatibility with BSD and GNU **locate**.

-P, --nofollow, -H

When checking whether files exist (if the **--existing** option is specified), do not follow trailing symbolic links. This causes broken symbolic links to be reported like other files.

This is the opposite of **--follow**.

-0, --null

Separate the entries on output using the ASCII NUL character instead of writing each entry on a separate line. This option is designed for interoperability with the **--null** option of GNU [xargs\(1\)](#).

-S, --statistics

Write statistics about each read database to standard output instead of searching for files and exit successfully.

-q, --quiet

Write no messages about errors encountered while reading and processing databases.

-r, --regexp *REGEXP*

Search for a basic regexp *REGEXP*. No *PATTERNS* are allowed if this option is used, but this option can be specified multiple times.

--regex

Interpret all *PATTERNS* as extended regexps.

-s, --stdio

Ignored, for compatibility with BSD and GNU **locate**.

-V, --version

Write information about the version and license of **locate** on standard output and exit successfully.

-w, --wholename

Match only the whole path name against the specified patterns.

This is the default behavior. The opposite can be specified using **--basename**.

EXAMPLES

To search for a file named exactly *NAME* (not **NAME**), use

```
locate -b 'NAME'
```

Because `*` is a globbing character, this disables the implicit replacement of *NAME* by **NAME**.

FILES

/var/lib/mlocate/mlocate.db

The database searched by default.

ENVIRONMENT**LOCATE_PATH**

Path to additional databases, added after the default database or the databases specified using the **--database** option.

NOTES

The order in which the requested databases are processed is unspecified, which allows **locate** to reorder the database path for security reasons.

locate attempts to be compatible to **slocate** (without the options used for creating databases) and GNU **locate**, in that order. This is the reason for the impractical default **--follow** option and for the confusing set of **--regex** and **--regexp** options.

The short spelling of the **-r** option is incompatible to GNU **locate**, where it corresponds to the **--regex** option. Use the long option names to avoid confusion.

The **LOCATE_PATH** environment variable replaces the default database in BSD and GNU **locate**, but it is added to other databases in this implementation and **slocate**.

AUTHOR

Miloslav Trmac <mitr@redhat.com>

SEE ALSO

[updatedb\(8\)](#)