

NAME

numfmt - Convert numbers from/to human-readable strings

SYNOPSIS

numfmt [*OPTION*]... [*NUMBER*]...

DESCRIPTION

Reformat *NUMBER*(s), or the numbers from standard input if none are specified.

Mandatory arguments to long options are mandatory for short options too.

--debug

print warnings about invalid input

-d, --delimiter=X

use X instead of whitespace for field delimiter

--field=N

replace the number in input field N (default is 1)

--format=FORMAT

use printf style floating-point FORMAT; see FORMAT below for details

--from=UNIT

auto-scale input numbers to UNITS; default is 'none'; see UNIT below

--from-unit=N

specify the input unit size (instead of the default 1)

--grouping

use locale-defined grouping of digits, e.g. 1,000,000 (which means it has no effect in the C/POSIX locale)

--header[=N]

print (without converting) the first N header lines; N defaults to 1 if not specified

--invalid=MODE

failure mode for invalid numbers: MODE can be: abort (default), fail, warn, ignore

--padding=N

pad the output to N characters; positive N will right-align; negative N will left-align; padding is ignored if the output is wider than N; the default is to automatically pad if a whitespace is found

--round=METHOD

use METHOD for rounding when scaling; METHOD can be: up, down, from-zero (default), towards-zero, nearest

--suffix=SUFFIX

add SUFFIX to output numbers, and accept optional SUFFIX in input numbers

--to=UNIT

auto-scale output numbers to UNITS; see UNIT below

--to-unit=N

the output unit size (instead of the default 1)

--help**--version**

output version information and exit

UNIT options:

none no auto-scaling is done; suffixes will trigger an error

auto accept optional single/two letter suffix:

```
1K = 1000, 1Ki = 1024, 1M = 1000000, 1Mi = 1048576,
si    accept optional single letter suffix:
      1K = 1000, 1M = 1000000, ...
iec   accept optional single letter suffix:
      1K = 1024, 1M = 1048576, ...
iec-i  accept optional two-letter suffix:
      1Ki = 1024, 1Mi = 1048576, ...
```

FORMAT must be suitable for printing one floating-point argument '%f'. Optional quote ('%f') will enable **--grouping** (if supported by current locale). Optional width value (%10f) will pad output. Optional zero (%010f) width will zero pad the number. Optional negative values (%-10f) will left align.

Exit status is 0 if all input numbers were successfully converted. By default, numfmt will stop at the first conversion error with exit status 2. With **--invalid='fail'** a warning is printed for each conversion error and the exit status is 2. With **--invalid='warn'** each conversion error is diagnosed, but the exit status is 0. With **--invalid='ignore'** conversion errors are not diagnosed and the exit status is 0.

EXAMPLES

```
$ numfmt --to=si 1000
-> 1.0K
$ numfmt --to=iec 2048
-> 2.0K
$ numfmt --to=iec-i 4096
-> 4.0Ki
$ echo 1K | numfmt --from=si
-> 1000
$ echo 1K | numfmt --from=iec
-> 1024
$ df | numfmt --header --field 2 --to=si
$ ls -l | numfmt --header --field 5 --to=iec
$ ls -lh | numfmt --header --field 5 --from=iec --padding=10
$ ls -lh | numfmt --header --field 5 --from=iec --format %10f
```

AUTHOR

Written by Assaf Gordon.

REPORTING BUGS

GNU coreutils online help: <<http://www.gnu.org/software/coreutils/>>
 Report numfmt translation bugs to <<http://translationproject.org/team/>>

COPYRIGHT

Copyright 2014 Free Software Foundation, Inc. License GPLv3+: GNU GPL version 3 or later
<<http://gnu.org/licenses/gpl.html>>.

This is free software: you are free to change and redistribute it. There is NO WARRANTY, to the extent permitted by law.

SEE ALSO

Full documentation at: <<http://www.gnu.org/software/coreutils/numfmt>>
or available locally via: info (coreutils) numfmt invocation