

**NAME**

postcat - show Postfix queue file contents

**SYNOPSIS**

**postcat** [-bdehnoqv] [-c *config\_dir*] [*files...*]

**DESCRIPTION**

The **postcat(1)** command prints the contents of the named *files* in human-readable form. The files are expected to be in Postfix queue file format. If no *files* are specified on the command line, the program reads from standard input.

By default, **postcat(1)** shows the envelope and message content, as if the options **-beh** were specified. To view message content only, specify **-bh** (Postfix 2.7 and later).

Options:

- b** Show body content. The **-b** option starts producing output at the first non-header line, and stops when the end of the message is reached.  
This feature is available in Postfix 2.7 and later.
- c *config\_dir***  
The **main.cf** configuration file is in the named directory instead of the default configuration directory.
- d** Print the decimal type of each record.
- e** Show message envelope content.  
This feature is available in Postfix 2.7 and later.
- h** Show message header content. The **-h** option produces output from the beginning of the message up to, but not including, the first non-header line.  
This feature is available in Postfix 2.7 and later.
- o** Print the queue file offset of each record.
- q** Search the Postfix queue for the named *files* instead of taking the names literally.  
This feature is available in Postfix 2.0 and later.
- v** Enable verbose logging for debugging purposes. Multiple **-v** options make the software increasingly verbose.

**DIAGNOSTICS**

Problems are reported to the standard error stream.

**ENVIRONMENT****MAIL\_CONFIG**

Directory with Postfix configuration files.

**CONFIGURATION PARAMETERS**

The following **main.cf** parameters are especially relevant to this program.

The text below provides only a parameter summary. See **postconf(5)** for more details including examples.

**config\_directory** (see '**postconf -d**' output)

The default location of the Postfix **main.cf** and **master.cf** configuration files.

**queue\_directory** (see '**postconf -d**' output)

The location of the Postfix top-level queue directory.

**FILES**

*/var/spool/postfix*, Postfix queue directory

**SEE ALSO**

[postconf\(5\)](#),  
Postfix configuration

**LICENSE**

The Secure Mailer license must be distributed with this software.

**AUTHOR(S)**

Wietse Venema  
IBM T.J. Watson Research  
P.O. Box 704  
Yorktown Heights, NY 10598, USA

Wietse Venema  
Google, Inc.  
111 8th Avenue  
New York, NY 10011, USA