

**NAME**

postlog - Postfix-compatible logging utility

**SYNOPSIS**

**postlog** [-iv] [-c *config\_dir*] [-p *priority*] [-t *tag*] [*text...*]

**DESCRIPTION**

The **postlog(1)** command implements a Postfix-compatible logging interface for use in, for example, shell scripts.

By default, **postlog(1)** logs the *text* given on the command line as one record. If no *text* is specified on the command line, **postlog(1)** reads from standard input and logs each input line as one record.

Logging is sent to **syslogd(8)**; when the standard error stream is connected to a terminal, logging is sent there as well.

The following options are implemented:

**-c** *config\_dir*

Read the **main.cf** configuration file in the named directory instead of the default configuration directory.

**-i** Include the process ID in the logging tag.

**-p** *priority* (default: **info**)

Specifies the logging severity: **info**, **warn**, **error**, **fatal**, or **panic**. With Postfix 3.1 and later, the program will pause for 1 second after reporting a **fatal** or **panic** condition, just like other Postfix programs.

**-t** *tag* Specifies the logging tag, that is, the identifying name that appears at the beginning of each logging record. A default tag is used when none is specified.

**-v** Enable verbose logging for debugging purposes. Multiple **-v** options make the software increasingly verbose.

**ENVIRONMENT**

MAIL\_CONFIG

Directory with the **main.cf** file.

**CONFIGURATION PARAMETERS**

The following **main.cf** parameters are especially relevant to this program.

The text below provides only a parameter summary. See **postconf(5)** for more details including examples.

**config\_directory** (see '**postconf -d**' output)

The default location of the Postfix **main.cf** and **master.cf** configuration files.

**syslog\_facility** (**mail**)

The syslog facility of Postfix logging.

**syslog\_name** (see '**postconf -d**' output)

The mail system name that is prepended to the process name in syslog records, so that "smtpd" becomes, for example, "postfix/smtpd".

**SEE ALSO**

[postconf\(5\)](#),

configuration parameters

[syslogd\(8\)](#), syslog daemon

**LICENSE**

The Secure Mailer license must be distributed with this software.

**AUTHOR(S)**

Wietse Venema

IBM T.J. Watson Research

P.O. Box 704  
Yorktown Heights, NY 10598, USA

Wietse Venema  
Google, Inc.  
111 8th Avenue  
New York, NY 10011, USA