

NAME

`io_cancel` - cancel an outstanding asynchronous I/O operation

SYNOPSIS

```
#include <linux/aio_abi.h> /* Defines needed types */  
  
int io_cancel(aio_context_t ctx_id, struct iocb *iocb,  
             struct io_event *result);
```

Note: There is no glibc wrapper for this system call; see NOTES.

DESCRIPTION

The `io_cancel()` system call attempts to cancel an asynchronous I/O operation previously submitted with `io_submit(2)`. The *io cb* argument describes the operation to be canceled and the *ctx_id* argument is the AIO context to which the operation was submitted. If the operation is successfully canceled, the event will be copied into the memory pointed to by *result* without being placed into the completion queue.

RETURN VALUE

On success, `io_cancel()` returns 0. For the failure return, see NOTES.

ERRORS**EAGAIN**

The *iocb* specified was not canceled.

EFAULT

One of the data structures points to invalid data.

EINVAL

The AIO context specified by *ctx_id* is invalid.

ENOSYS

`io_cancel()` is not implemented on this architecture.

VERSIONS

The asynchronous I/O system calls first appeared in Linux 2.5.

CONFORMING TO

`io_cancel()` is Linux-specific and should not be used in programs that are intended to be portable.

NOTES

Glibc does not provide a wrapper function for this system call. You could invoke it using `syscall(2)`. But instead, you probably want to use the `io_cancel()` wrapper function provided by *libaio*.

Note that the *libaio* wrapper function uses a different type (*io_context_t*) for the *ctx_id* argument. Note also that the *libaio* wrapper does not follow the usual C library conventions for indicating errors: on error it returns a negated error number (the negative of one of the values listed in ERRORS). If the system call is invoked via `syscall(2)`, then the return value follows the usual conventions for indicating an error: -1, with *errno* set to a (positive) value that indicates the error.

SEE ALSO

`io_destroy(2)`, `io_getevents(2)`, `io_setup(2)`, `io_submit(2)`, `aio(7)`

COLOPHON

This page is part of release 3.74 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <http://www.kernel.org/doc/man-pages/>.