

NAME

`io_setup` - create an asynchronous I/O context

SYNOPSIS

```
#include <linux/aio_abi.h> /* Defines needed types */
```

```
int io_setup(unsigned nr_events, aio_context_t *ctx_idp);
```

Note: There is no glibc wrapper for this system call; see NOTES.

DESCRIPTION

The `io_setup()` system call creates an asynchronous I/O context suitable for concurrently processing `nr_events` operations. The `ctx_idp` argument must not point to an AIO context that already exists, and must be initialized to 0 prior to the call. On successful creation of the AIO context, `*ctx_idp` is filled in with the resulting handle.

RETURN VALUE

On success, `io_setup()` returns 0. For the failure return, see NOTES.

ERRORS**EAGAIN**

The specified `nr_events` exceeds the user's limit of available events, as defined in `/proc/sys/fs/aio-max-nr`.

EFAULT

An invalid pointer is passed for `ctx_idp`.

EINVAL

`ctx_idp` is not initialized, or the specified `nr_events` exceeds internal limits. `nr_events` should be greater than 0.

ENOMEM

Insufficient kernel resources are available.

ENOSYS

`io_setup()` is not implemented on this architecture.

VERSIONS

The asynchronous I/O system calls first appeared in Linux 2.5.

CONFORMING TO

`io_setup()` is Linux-specific and should not be used in programs that are intended to be portable.

NOTES

Glibc does not provide a wrapper function for this system call. You could invoke it using `syscall(2)`. But instead, you probably want to use the `io_setup()` wrapper function provided by `libaio`.

Note that the `libaio` wrapper function uses a different type (`io_context_t *`) for the `ctx_idp` argument. Note also that the `lib aio` wrapper does not follow the usual C library conventions for indicating errors: on error it returns a negated error number (the negative of one of the values listed in ERRORS). If the system call is invoked via `syscall(2)`, then the return value follows the usual conventions for indicating an error: -1, with `errno` set to a (positive) value that indicates the error.

SEE ALSO

[io_cancel\(2\)](#), [io_destroy\(2\)](#), [io_getevents\(2\)](#), [io_submit\(2\)](#), [aio\(7\)](#)

COLOPHON

This page is part of release 3.74 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <http://www.kernel.org/doc/man-pages/>.