

NAME

`sched_setscheduler`, `sched_getscheduler` - set and get scheduling policy/parameters

SYNOPSIS

```
#include <sched.h>

int sched_setscheduler(pid_t pid, int policy,
    const struct sched_param *param);

int sched_getscheduler(pid_t pid);
```

DESCRIPTION

The `sched_setscheduler()` system call sets both the scheduling policy and parameters for the thread whose ID is specified in *pid*. If *pid* equals zero, the scheduling policy and parameters of the calling thread will be set.

The scheduling parameters are specified in the *param* argument, which is a pointer to a structure of the following form:

```
struct sched_param {
    int sched_priority;
};
```

In the current implementation, the structure contains only one field, *sched_priority*. The interpretation of *param* depends on the selected policy.

Currently, Linux supports the following "normal" (i.e., non-real-time) scheduling policies as values that may be specified in *policy*:

SCHED_OTHER

the standard round-robin time-sharing policy;

SCHED_BATCH

for "batch" style execution of processes; and

SCHED_IDLE for running *very* low priority background jobs.

For each of the above policies, *param->sched_priority* must be 0.

Various "real-time" policies are also supported, for special time-critical applications that need precise control over the way in which runnable threads are selected for execution. For the rules governing when a process may use these policies, see [sched\(7\)](#). The real-time policies that may be specified in *policy* are:

SCHED_FIFO a first-in, first-out policy; and

SCHED_RR a round-robin policy.

For each of the above policies, *param->sched_priority* specifies a scheduling priority for the thread. This is a number in the range returned by calling [sched_get_priority_min\(2\)](#) and [sched_get_priority_max\(2\)](#) with the specified *policy*. On Linux, these system calls return, respectively, 1 and 99.

Since Linux 2.6.32, the **SCHED_RESET_ON_FORK** flag can be ORed in *policy* when calling `sched_setscheduler()`. As a result of including this flag, children created by [fork\(2\)](#) do not inherit privileged scheduling policies. See [sched\(7\)](#) for details.

`sched_getscheduler()` returns the current scheduling policy of the thread identified by *pid*. If *pid* equals zero, the policy of the calling thread will be retrieved.

RETURN VALUE

On success, `sched_setscheduler()` returns zero. On success, `sched_getscheduler()` returns the policy for the thread (a nonnegative integer). On error, both calls return -1, and *errno* is set appropriately.

ERRORS**EINVAL**

Invalid arguments: *pid* is negative or *param* is NULL.

EINVAL

(`sched_setscheduler()`) *policy* is not one of the recognized policies.

EINVAL

(`sched_setscheduler()`) *param* does not make sense for the specified *policy*.

EPERM

The calling thread does not have appropriate privileges.

ESRCH

The thread whose ID is *pid* could not be found.

CONFORMING TO

POSIX.1-2001, POSIX.1-2008 (but see BUGS below). The **SCHED_BATCH** and **SCHED_IDLE** policies are Linux-specific.

NOTES

Further details of the semantics of all of the above "normal" and "real-time" scheduling policies can be found in the [sched\(7\)](#) manual page. That page also describes an additional policy, **SCHED_DEADLINE**, which is settable only via [sched_setattr\(2\)](#).

POSIX systems on which `sched_setscheduler()` and `sched_getscheduler()` are available define **_POSIX_PRIORITY_SCHEDULING** in `<unistd.h>`.

POSIX.1 does not detail the permissions that an unprivileged thread requires in order to call `sched_setscheduler()`, and details vary across systems. For example, the Solaris 7 manual page says that the real or effective user ID of the caller must match the real user ID or the save set-user-ID of the target.

The scheduling policy and parameters are in fact per-thread attributes on Linux. The value returned from a call to [gettid\(2\)](#) can be passed in the argument *pid*. Specifying *pid* as 0 will operate on the attributes of the calling thread, and passing the value returned from a call to [getpid\(2\)](#) will operate on the attributes of the main thread of the thread group. (If you are using the POSIX threads API, then use [pthread_setschedparam\(3\)](#), [pthread_getschedparam\(3\)](#), and [pthread_setschedprio\(3\)](#), instead of the `sched_*(2)` system calls.)

BUGS

POSIX.1 says that on success, `sched_setscheduler()` should return the previous scheduling policy. Linux `sched_setscheduler()` does not conform to this requirement, since it always returns 0 on success.

SEE ALSO

[chrt\(1\)](#), [nice\(2\)](#), [sched_get_priority_max\(2\)](#), [sched_get_priority_min\(2\)](#), [sched_getaffinity\(2\)](#), [sched_getattr\(2\)](#), [sched_getparam\(2\)](#), [sched_rr_get_interval\(2\)](#), [sched_setaffinity\(2\)](#), [sched_setattr\(2\)](#), [sched_setparam\(2\)](#), [sched_yield\(2\)](#), [setpriority\(2\)](#), [capabilities\(7\)](#), [cpuset\(7\)](#), [sched\(7\)](#)

COLOPHON

This page is part of release 4.10 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.