

NAME

`fpurge`, `__fpurge` - purge a stream

SYNOPSIS

```
/* unsupported */
#include <stdio.h>

int fpurge(FILE *stream);

/* supported */
#include <stdio.h>
#include <stdio_ext.h>

void __fpurge(FILE *stream);
```

DESCRIPTION

The function `fpurge()` clears the buffers of the given stream. For output streams this discards any unwritten output. For input streams this discards any input read from the underlying object but not yet obtained via `getc(3)`; this includes any text pushed back via `ungetc(3)`. See also `fflush(3)`.

The function `__fpurge()` does precisely the same, but without returning a value.

RETURN VALUE

Upon successful completion `fpurge()` returns 0. On error, it returns -1 and sets `errno` appropriately.

ERRORS**EBADF**

stream is not an open stream.

CONFORMING TO

These functions are nonstandard and not portable. The function `fpurge()` was introduced in 4.4BSD and is not available under Linux. The function `__fpurge()` was introduced in Solaris, and is present in glibc 2.1.95 and later.

NOTES

Usually it is a mistake to want to discard input buffers.

SEE ALSO

[fflush\(3\)](#), [setbuf\(3\)](#), [stdio_ext\(3\)](#)

COLOPHON

This page is part of release 3.74 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <http://www.kernel.org/doc/man-pages/>.