

NAME

`aiowrite` - asynchronous write

SYNOPSIS

```
#include <aio.h>
```

```
int aiowrite(struct aiocb *aiocbp);
```

Link with `-lrt`.

DESCRIPTION

The `aiowrite()` function queues the I/O request described by the buffer pointed to by `aiocbp`. This function is the asynchronous analog of `write(2)`. The arguments of the call

```
write(fd, buf, count)
```

correspond (in order) to the fields `aiocbp->aio_fildes`, `aiocbp->aio_buf`, and `aiocbp->aio_nbytes` of the structure pointed to by `aiocbp`. (See [aio\(7\)](#) for a description of the `aiocb` structure.)

If `O_APPEND` is not set, the data is written starting at the absolute file offset `aiocbp->aio_offset`, regardless of the current file offset. If `O_APPEND` is set, data is written at the end of the file in the same order as `aiowrite()` calls are made. After the call, the value of the current file offset is unspecified.

The "asynchronous" means that this call returns as soon as the request has been enqueued; the write may or may not have completed when the call returns. One tests for completion using [aio_error\(3\)](#). The return status of a completed I/O operation can be obtained via [aio_return\(3\)](#). Asynchronous notification of I/O completion can be obtained by setting `aiocbp->aio_sigevent` appropriately; see [sigevent\(7\)](#) for details.

If `_POSIX_PRIORITYIO` is defined, and this file supports it, then the asynchronous operation is submitted at a priority equal to that of the calling process minus `aiocbp->aio_reqprio`.

The field `aiocbp->aio_lio_opcode` is ignored.

No data is written to a regular file beyond its maximum offset.

RETURN VALUE

On success, 0 is returned. On error, the request is not enqueued, -1 is returned, and `errno` is set appropriately. If an error is detected only later, it will be reported via [aio_return\(3\)](#) (returns status -1) and [aio_error\(3\)](#) (error status—whatever one would have gotten in `errno`, such as **EBADF**).

ERRORS**EAGAIN**

Out of resources.

EBADF

`aiocbp->aio_fildes` is not a valid file descriptor open for writing.

EFBIG

The file is a regular file, we want to write at least one byte, but the starting position is at or beyond the maximum offset for this file.

EINVAL

One or more of `aiocbp->aio_offset`, `aiocbp->aio_reqprio`, `aiocbp->aio_nbytes` are invalid.

ENOSYS

`aiowrite()` is not implemented.

VERSIONS

The `aiowrite()` function is available since glibc 2.1.

CONFORMING TO

POSIX.1-2001, POSIX.1-2008.

NOTES

It is a good idea to zero out the control block before use. The control block must not be changed while the write operation is in progress. The buffer area being written out must not be accessed during the operation

or undefined results may occur. The memory areas involved must remain valid.

Simultaneous I/O operations specifying the same *aio_cb* structure produce undefined results.

SEE ALSO

[aio_cancel\(3\)](#), [aio_error\(3\)](#), [aio_fsync\(3\)](#), [aio_read\(3\)](#), [aio_return\(3\)](#), [aio_suspend\(3\)](#), [lio_listio\(3\)](#), [aio\(7\)](#)

COLOPHON

This page is part of release 3.74 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <http://www.kernel.org/doc/man-pages/>.