

NAME

basename, dirname - parse pathname components

SYNOPSIS

```
#include <libgen.h>

char *dirname(char *path);

char *basename(char *path);
```

DESCRIPTION

Warning: there are two different functions **basename()** - see below.

The functions **dirname()** and **basename()** break a null-terminated pathname string into directory and filename components. In the usual case, **dirname()** returns the string up to, but not including, the final /, and **basename()** returns the component following the final /. Trailing / characters are not counted as part of the pathname.

If *path* does not contain a slash, **dirname()** returns the string . while **basename()** returns a copy of *path*. If *path* is the string /, then both **dirname()** and **basename()** return the string /. If *path* is a null pointer or points to an empty string, then both **dirname()** and **basename()** return the string ..

Concatenating the string returned by **dirname()**, a /, and the string returned by **basename()** yields a complete pathname.

Both **dirname()** and **basename()** may modify the contents of *path*, so it may be desirable to pass a copy when calling one of these functions.

These functions may return pointers to statically allocated memory which may be overwritten by subsequent calls. Alternatively, they may return a pointer to some part of *path*, so that the string referred to by *path* should not be modified or freed until the pointer returned by the function is no longer required.

The following list of examples (taken from SUSv2) shows the strings returned by **dirname()** and **basename()** for different paths:

path	dirname	basename
/usr/lib	/usr	lib
/usr/	/	usr
usr	.	usr
/	/	/
.	.	.
..	.	..

RETURN VALUE

Both **dirname()** and **basename()** return pointers to null-terminated strings. (Do not pass these pointers to [free\(3\)](#).)

ATTRIBUTES

Multithreading (see [pthreads\(7\)](#))

The **basename()** and **dirname()** functions are thread-safe.

CONFORMING TO

POSIX.1-2001.

NOTES

There are two different versions of **basename()** - the POSIX version described above, and the GNU version, which one gets after

```
#define _GNU_SOURCE /* See feature\_test\_macros\(7\) */
#include <string.h>
```

The GNU version never modifies its argument, and returns the empty string when *path* has a trailing slash, and in particular also when it is `/`. There is no GNU version of `dirname()`.

With glibc, one gets the POSIX version of `basename()` when `<libgen.h>` is included, and the GNU version otherwise.

BUGS

In the glibc implementation of the POSIX versions of these functions they modify their argument, and segfault when called with a static string like `/usr/`. Before glibc 2.2.1, the glibc version of `dirname()` did not correctly handle pathnames with trailing `/` characters, and generated a segfault if given a NULL argument.

EXAMPLE

```
char *dir, *base, *bname, *dname;
char *path = /etc/passwd;

dir = strdup(path);
base = strdup(path);
dname = dirname(dir);
bname = basename(base);
printf(dirname=%s, basename=%sn, dname, bname);
```

SEE ALSO

[basename\(1\)](#), [dirname\(1\)](#)

COLOPHON

This page is part of release 3.74 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <http://www.kernel.org/doc/man-pages/>.