

**NAME**

`acos`, `acosf`, `acosl` - complex arc cosine

**SYNOPSIS**

```
#include <complex.h>
```

```
double complex acos(double complex z);
```

```
float complex acosf(float complex z);
```

```
long double complex acosl(long double complex z);
```

Link with `-lm`.

**DESCRIPTION**

The `acos()` function calculates the complex arc cosine of  $z$ . If  $y = c \operatorname{acos}(z)$ , then  $z = c \operatorname{ccos}(y)$ . The real part of  $y$  is chosen in the interval  $[0, \pi]$ .

One has:

$$\operatorname{acos}(z) = -i * \operatorname{clog}(z + i * \operatorname{csqrt}(1 - z * z))$$
**VERSIONS**

These functions first appeared in glibc in version 2.1.

**CONFORMING TO**

C99.

**EXAMPLE**

```
/* Link with -lm */
#include <complex.h>
#include <stdlib.h>
#include <unistd.h>
#include <stdio.h>

int
main(int argc, char *argv[])
{
    double complex z, c, f;
    double complex i = I;

    if (argc != 3) {
        fprintf(stderr, Usage: %s <real> <imag>n, argv[0]);
        exit(EXIT_FAILURE);
    }

    z = atof(argv[1]) + atof(argv[2]) * I;

    c = acos(z);

    printf(acos() = %6.3f %6.3f*in, creal(c), cimag(c));

    f = -i * clog(z + i * csqrt(1 - z * z));

    printf(formula = %6.3f %6.3f*in, creal(f), cimag(f));

    exit(EXIT_SUCCESS);
}
```

**SEE ALSO**

[ccos\(3\)](#), [clog\(3\)](#), [complex\(7\)](#)

**COLOPHON**

This page is part of release 3.74 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <http://www.kernel.org/doc/man-pages/>.