

**NAME**

catan, catanf, catanl - complex arc tangents

**SYNOPSIS**

```
#include <complex.h>
```

```
double complex catan(double complex z);
```

```
float complex catanf(float complex z);
```

```
long double complex catanl(long double complex z);
```

Link with *-lm*.

**DESCRIPTION**

The **catan()** function calculates the complex arc tangent of *z*. If  $y = c \operatorname{atan}(z)$ , then  $z = c \operatorname{atan}(y)$ . The real part of *y* is chosen in the interval  $[-\pi/2, \pi/2]$ .

One has:

$$\operatorname{catan}(z) = (\operatorname{clog}(1 + i * z) - \operatorname{clog}(1 - i * z)) / (2 * i)$$

**VERSIONS**

These functions first appeared in glibc in version 2.1.

**CONFORMING TO**

C99.

**EXAMPLE**

```
/* Link with -lm */
#include <complex.h>
#include <stdlib.h>
#include <unistd.h>
#include <stdio.h>

int
main(int argc, char *argv[])
{
    double complex z, c, f;
    double complex i = I;

    if (argc != 3) {
        fprintf(stderr, Usage: %s <real> <imag>n, argv[0]);
        exit(EXIT_FAILURE);
    }

    z = atof(argv[1]) + atof(argv[2]) * I;

    c = catan(z);
    printf(catan() = %6.3f %6.3f*in, creal(c), cimag(c));

    f = (clog(1 + i * z) - clog(1 - i * z)) / (2 * i);
    printf(formula = %6.3f %6.3f*in, creal(f2), cimag(f2));

    exit(EXIT_SUCCESS);
}
```

**SEE ALSO**

[ccos\(3\)](#), [clog\(3\)](#), [ctan\(3\)](#), [complex\(7\)](#)

**COLOPHON**

This page is part of release 3.74 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <http://www.kernel.org/doc/man-pages/>.