

NAME

getrpcent, getrpcbyname, getrpcbnumber, setrpcent, endrpcent - get RPC entry

SYNOPSIS

```
#include <netdb.h>

struct rpcent *getrpcent(void);

struct rpcent *getrpcbyname(const char *name);

struct rpcent *getrpcbnumber(int number);

void setrpcent(int stayopen);

void endrpcent(void);
```

DESCRIPTION

The **getrpcent()**, **getrpcbyname()**, and **getrpcbnumber()** functions each return a pointer to an object with the following structure containing the broken-out fields of an entry in the RPC program number data base.

```
struct rpcent {
    char *r_name; /* name of server for this RPC program */
    char **r_aliases; /* alias list */
    long r_number; /* RPC program number */
};
```

The members of this structure are:

r_name The name of the server for this RPC program.
r_aliases A NULL-terminated list of alternate names for the RPC program.
r_number The RPC program number for this service.

The **getrpcent()** function reads the next entry from the database. A connection is opened to the database if necessary.

The **setrpcent()** function opens a connection to the database, and sets the next entry to the first entry. If *stayopen* is nonzero, then the connection to the database will not be closed between calls to one of the **getrpc***() functions.

The **endrpcent()** function closes the connection to the database.

The **getrpcbyname()** and **getrpcbnumber()** functions sequentially search from the beginning of the file until a matching RPC program name or program number is found, or until end-of-file is encountered.

RETURN VALUE

On success, **getrpcent()**, **getrpcbyname()**, and **getrpcbnumber()** return a pointer to a statically allocated *rpcent* structure. NULL is returned on EOF or error.

FILES

/etc/rpc
 RPC program number database.

CONFORMING TO

Not in POSIX.1-2001. Present on the BSDs, Solaris, and many other systems.

BUGS

All information is contained in a static area so it must be copied if it is to be saved.

SEE ALSO

[getrpcent_r\(3\)](#), [rpc\(5\)](#), [rpcinfo\(8\)](#), [ypserv\(8\)](#)

COLOPHON

This page is part of release 3.74 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <http://www.kernel.org/doc/man-pages/>.