

**NAME**

getcwd, getwd, get\_current\_dir\_name - get current working directory

**SYNOPSIS**

```
#include <unistd.h>

char *getcwd(char *buf, size_t size);

char *getwd(char *buf);

char *get_current_dir_name(void);
```

Feature Test Macro Requirements for glibc (see [feature\\_test\\_macros\(7\)](#)):

```
get_current_dir_name():
    _GNU_SOURCE
```

```
getwd():
```

Since glibc 2.12:

```
    _BSD_SOURCE ||
    ( _XOPEN_SOURCE >= 500 ||
      _XOPEN_SOURCE && _XOPEN_SOURCE_EXTENDED) &&
    !(_POSIX_C_SOURCE >= 200809L || _XOPEN_SOURCE >= 700)
```

Before glibc 2.12:

```
    _BSD_SOURCE || _XOPEN_SOURCE >= 500 ||
    _XOPEN_SOURCE && _XOPEN_SOURCE_EXTENDED
```

**DESCRIPTION**

These functions return a null-terminated string containing an absolute pathname that is the current working directory of the calling process. The pathname is returned as the function result and via the argument *buf*, if present.

The `getcwd()` function copies an absolute pathname of the current working directory to the array pointed to by *buf*, which is of length *size*.

If the length of the absolute pathname of the current working directory, including the terminating null byte, exceeds *size* bytes, NULL is returned, and *errno* is set to **ERANGE**; an application should check for this error, and allocate a larger buffer if necessary.

As an extension to the POSIX.1-2001 standard, glibc's `getcwd()` allocates the buffer dynamically using [malloc\(3\)](#) if *buf* is NULL. In this case, the allocated buffer has the length *size* unless *size* is zero, when *buf* is allocated as big as necessary. The caller should [free\(3\)](#) the returned buffer.

`get_current_dir_name()` will [malloc\(3\)](#) an array big enough to hold the absolute pathname of the current working directory. If the environment variable **PWD** is set, and its value is correct, then that value will be returned. The caller should [free\(3\)](#) the returned buffer.

`getwd()` does not [malloc\(3\)](#) any memory. The *buf* argument should be a pointer to an array at least **PATH\_MAX** bytes long. If the length of the absolute pathname of the current working directory, including the terminating null byte, exceeds **PATH\_MAX** bytes, NULL is returned, and *errno* is set to **ENAMETOOLONG**. (Note that on some systems, **PATH\_MAX** may not be a compile-time constant; furthermore, its value may depend on the filesystem, see [pathconf\(3\)](#).) For portability and security reasons, use of `getwd()` is deprecated.

**RETURN VALUE**

On success, these functions return a pointer to a string containing the pathname of the current working directory. In the case of `getcwd()` and `getwd()` this is the same value as *buf*.

On failure, these functions return NULL, and *errno* is set to indicate the error. The contents of the array pointed to by *buf* are undefined on error.

## ERRORS

### EACCES

Permission to read or search a component of the filename was denied.

### EFAULT

*buf* points to a bad address.

### EINVAL

The *size* argument is zero and *buf* is not a null pointer.

### EINVAL

**getwd()**: *buf* is NULL.

### ENAMETOOLONG

**getwd()**: The size of the null-terminated absolute pathname string exceeds **PATH\_MAX** bytes.

### ENOENT

The current working directory has been unlinked.

### ERANGE

The *size* argument is less than the length of the absolute pathname of the working directory, including the terminating null byte. You need to allocate a bigger array and try again.

## CONFORMING TO

**getwd()** conforms to POSIX.1-2001. Note however that POSIX.1-2001 leaves the behavior of **getwd()** unspecified if *buf* is NULL.

**getwd()** is present in POSIX.1-2001, but marked LEGACY. POSIX.1-2008 removes the specification of **getwd()**. Use **getcwd()** instead. POSIX.1-2001 does not define any errors for **getwd()**.

**get\_current\_dir\_name()** is a GNU extension.

## NOTES

Under Linux, the function **getcwd()** is a system call (since 2.1.92). On older systems it would query */proc/self/cwd*. If both system call and *proc* filesystem are missing, a generic implementation is called. Only in that case can these calls fail under Linux with **EACCES**.

These functions are often used to save the location of the current working directory for the purpose of returning to it later. Opening the current directory (.) and calling [fchdir\(2\)](#) to return is usually a faster and more reliable alternative when sufficiently many file descriptors are available, especially on platforms other than Linux.

## SEE ALSO

[chdir\(2\)](#), [fchdir\(2\)](#), [open\(2\)](#), [unlink\(2\)](#), [free\(3\)](#), [malloc\(3\)](#)

## COLOPHON

This page is part of release 3.74 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <http://www.kernel.org/doc/man-pages/>.