

NAME

getpw - reconstruct password line entry

SYNOPSIS

```
#define _GNU_SOURCE /* See feature\_test\_macros\(7\) */
#include <sys/types.h>
#include <pwd.h>

int getpw(uid_t uid, char *buf);
```

DESCRIPTION

The `getpw()` function reconstructs the password line entry for the given user ID *uid* in the buffer *buf*. The returned buffer contains a line of format

name:passwd:uid:gid:gecos:dir:shell

The *passwd* structure is defined in *<pwd.h>* as follows:

```
struct passwd {
    char *pw_name; /* username */
    char *pw_passwd; /* user password */
    uid_t pw_uid; /* user ID */
    gid_t pw_gid; /* group ID */
    char *pw_gecos; /* user information */
    char *pw_dir; /* home directory */
    char *pw_shell; /* shell program */
};
```

For more information about the fields of this structure, see [passwd\(5\)](#).

RETURN VALUE

The `getpw()` function returns 0 on success; on error, it returns -1, and *errno* is set to indicate the error.

ERRORS**EINVAL**

buf is NULL.

ENOENT

No user corresponding to *uid*.

ENOMEM

Insufficient memory to allocate *passwd* structure.

FILES

/etc/passwd
password database file

CONFORMING TO

SVr2.

BUGS

The `getpw()` function is dangerous as it may overflow the provided buffer *buf*. It is obsoleted by [getpwuid\(3\)](#).

SEE ALSO

[endpwent\(3\)](#), [fgetpwent\(3\)](#), [getpwent\(3\)](#), [getpwnam\(3\)](#), [getpwuid\(3\)](#), [putpwent\(3\)](#), [setpwent\(3\)](#), [passwd\(5\)](#)

COLOPHON

This page is part of release 3.74 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <http://www.kernel.org/doc/man-pages/>.