

NAME

getrpcent_r, getrpcbyname_r, getrpcbynumber_r - get RPC entry (reentrant)

SYNOPSIS

```
#include <netdb.h>
```

```
int getrpcent_r(struct rpcent *result_buf, char *buf,
               size_t buflen, struct rpcent **result);
```

```
int getrpcbyname_r(const char *name,
                  struct rpcent *result_buf, char *buf,
                  size_t buflen, struct rpcent **result);
```

```
int getrpcbynumber_r(int number,
                    struct rpcent *result_buf, char *buf,
                    size_t buflen, struct rpcent **result);
```

Feature Test Macro Requirements for glibc (see [feature_test_macros\(7\)](#)):

```
getrpcent_r(), getrpcbyname_r(), getrpcbynumber_r():
    _BSD_SOURCE || _SVID_SOURCE
```

DESCRIPTION

The `getrpcent_r()`, `getrpcbyname_r()`, and `getrpcbynumber_r()` functions are the reentrant equivalents of, respectively, [getrpcent\(3\)](#), [getrpcbyname\(3\)](#), and [getrpcbynumber\(3\)](#). They differ in the way that the `rpcent` structure is returned, and in the function calling signature and return value. This manual page describes just the differences from the nonreentrant functions.

Instead of returning a pointer to a statically allocated `rpcent` structure as the function result, these functions copy the structure into the location pointed to by `result_buf`.

The `buf` array is used to store the string fields pointed to by the returned `rpcent` structure. (The nonreentrant functions allocate these strings in static storage.) The size of this array is specified in `buflen`. If `buf` is too small, the call fails with the error **ERANGE**, and the caller must try again with a larger buffer. (A buffer of length 1024 bytes should be sufficient for most applications.)

If the function call successfully obtains an RPC record, then `*result` is set pointing to `result_buf`; otherwise, `*result` is set to `NULL`.

RETURN VALUE

On success, these functions return 0. On error, they return one of the positive error numbers listed in [ERRORS](#).

On error, record not found (`getrpcbyname_r()`, `getrpcbynumber_r()`), or end of input (`getrpcent_r()`) `result` is set to `NULL`.

ERRORS**ENOENT**

(`getrpcent_r()`) No more records in database.

ERANGE

`buf` is too small. Try again with a larger buffer (and increased `buflen`).

CONFORMING TO

These functions are GNU extensions. Functions with similar names exist on some other systems, though typically with different calling signatures.

SEE ALSO

[getrpcent\(3\)](#), [rpc\(5\)](#)

COLOPHON

This page is part of release 3.74 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at

<http://www.kernel.org/doc/man-pages/>.