

NAME

`fgetc`, `getc` - read a wide character from a FILE stream

SYNOPSIS

```
#include <stdio.h>
#include <wchar.h>

wint_t fgetc(FILE *stream);
wint_t getc(FILE *stream);
```

DESCRIPTION

The `fgetc()` function is the wide-character equivalent of the `fgetc(3)` function. It reads a wide character from *stream* and returns it. If the end of stream is reached, or if `ferror(stream)` becomes true, it returns **WEOF**. If a wide-character conversion error occurs, it sets `errno` to **EILSEQ** and returns **WEOF**.

The `getc()` function or macro functions identically to `fgetc()`. It may be implemented as a macro, and may evaluate its argument more than once. There is no reason ever to use it.

For nonlocking counterparts, see [unlocked_stdio\(3\)](#).

RETURN VALUE

The `fgetc()` function returns the next wide-character from the stream, or **WEOF**. In the event of an error, `errno` is set to indicate the cause.

ERRORS

Apart from the usual ones, there is

EILSEQ

The data obtained from the input stream does not form a valid character.

CONFORMING TO

C99, POSIX.1-2001.

NOTES

The behavior of `fgetc()` depends on the **LC_CTYPE** category of the current locale.

In the absence of additional information passed to the `fopen(3)` call, it is reasonable to expect that `fgetc()` will actually read a multibyte sequence from the stream and then convert it to a wide character.

SEE ALSO

[fgetws\(3\)](#), [fputc\(3\)](#), [ungetc\(3\)](#), [unlocked_stdio\(3\)](#)

COLOPHON

This page is part of release 3.74 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <http://www.kernel.org/doc/man-pages/>.