

**NAME**

none - undocumented library functions

**SYNOPSIS**

Undocumented library functions

**DESCRIPTION**

This man page mentions those library functions which are implemented in the standard libraries but not yet documented in man pages.

**Solicitation**

If you have information about these functions, please look in the source code, write a man page (using a style similar to that of the other Linux section 3 man pages), and send it to [mtk.man-pages@gmail.com](mailto:mtk.man-pages@gmail.com) for inclusion in the next man page release.

**The list**

```
authdes_create(3), authdes_getucred(3), authdes_pk_create(3), clntunix_create(3),
creat64(3), dn_skipname(3), fcrypt(3), fp_nquery(3), fp_query(3), fp_resstat(3),
freading(3), freopen64(3), fseeko64(3), ftello64(3), ftw64(3), fwscanf(3),
get_avphys_pages(3), getdirentries64(3), getmsg(3), getnetname(3), get\_nprocs\(3\),
get\_nprocs\_conf\(3\), get_phys_pages(3), getpublickey(3), getsecretkey(3), h_errlist(3),
host2netname(3), hostalias(3), inet_nsap_addr(3), inet_nsap_ntoa(3), init_des(3),
libc_nls_init(3), lio\_listio\(3\), mstats(3), netname2host(3), netname2user(3), nlist(3),
obstack_free(3), parse_printf_format(3), p_cdbname(3), p_cdnname(3), p_class(3),
p_fqname(3), p_option(3), p_query(3), printf_size(3), printf_size_info(3), p_rr(3),
p_time(3), p_type(3), putlong(3), putshort(3), re_compile_fastmap(3), re_compile_pattern(3),
register_printf_function(3), re_match(3), re_match_2(3), re_rx_search(3), re_search(3),
re_search_2(3), re_set_registers(3), re_set_syntax(3), res_send_setqhook(3),
res_send_setrhook(3), ruserpass(3), setfileno(3), sethostfile(3), svc_exit(3),
svcudp_enablecache(3), tell(3), tr_break(3), tzsetwall(3), ufc_dofinalperm(3),
ufc_doit(3), user2netname(3), vlimit\(3\), vtimes\(3\), wcschrnul(3), wcsftime(3),
wscanf(3), xdr_authdes_cred(3), xdr_authdes_verf(3), xdr_cryptkeyarg(3),
xdr_cryptkeyres(3), xdr_datum(3), xdr_des_block(3), xdr_domainname(3), xdr_getcredres(3),
xdr_keybuf(3), xdr_keystatus(3), xdr_mapname(3), xdr_netnamestr(3), xdr_netobj(3),
xdr_passwd(3), xdr_peername(3), xdr_rmtcall_args(3), xdr_rmtcall_res(3),
xdr_unixcred(3), xdr_yp_buf(3), xdr_yp_inaddr(3), xdr_ypbind_binding(3),
xdr_ypbind_resp(3), xdr_ypbind_resptype(3), xdr_ypbind_setdom(3),
xdr_ypdelete_args(3), xdr_ypmaplist(3), xdr_ypmaplist_str(3), xdr_yppasswd(3),
xdr_ypreq_key(3), xdr_ypreq_nokey(3), xdr_ypresp_all(3), xdr_ypresp_all_seq(3),
xdr_ypresp_key_val(3), xdr_ypresp_maplist(3), xdr_ypresp_master(3),
xdr_ypresp_order(3), xdr_ypresp_val(3), xdr_ypstat(3), xdr_ypupdate_args(3),
yp_all(3), yp_bind(3), yperr_string(3), yp_first(3), yp_get_default_domain(3),
yp_maplist(3), yp_master(3), yp_match(3), yp_next(3), yp_order(3), ypprot_err(3),
yp_unbind(3), yp_update(3)
```

**COLOPHON**

This page is part of release 3.74 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <http://www.kernel.org/doc/man-pages/>.