

NAME

pthread_setname_np, pthread_getname_np - set/get the name of a thread

SYNOPSIS

```
#define _GNU_SOURCE /* See feature\_test\_macros\(7\)
*/
#include <pthread.h>
int pthread_setname_np(pthread_t thread, const char *name);
int pthread_getname_np(pthread_t thread,
    char *name, size_t len);
```

Compile and link with `-pthread`.

DESCRIPTION

By default, all the threads created using `pthread_create()` inherit the program name. The `pthread_setname_np()` function can be used to set a unique name for a thread, which can be useful for debugging multithreaded applications. The thread name is a meaningful C language string, whose length is restricted to 16 characters, including the terminating null byte (`'\0'`). The *thread* argument specifies the thread whose name is to be changed; *name* specifies the new name.

The `pthread_getname_np()` function can be used to retrieve the name of the thread. The *thread* argument specifies the thread whose name is to be retrieved. The buffer *name* is used to return the thread name; *len* specifies the number of bytes available in *name*. The buffer specified by *name* should be at least 16 characters in length. The returned thread name in the output buffer will be null terminated.

RETURN VALUE

On success, these functions return 0; on error, they return a nonzero error number.

ERRORS

The `pthread_setname_np()` function can fail with the following error:

ERANGE

The length of the string specified pointed to by *name* exceeds the allowed limit.

The `pthread_getname_np()` function can fail with the following error:

ERANGE

The buffer specified by *name* and *len* is too small to hold the thread name.

If either of these functions fails to open `/proc/self/task/[tid]/comm`, then the call may fail with one of the errors described in [open\(2\)](#).

VERSIONS

These functions first appeared in glibc in version 2.12.

ATTRIBUTES

For an explanation of the terms used in this section, see [attributes\(7\)](#).

Interface	Attribute	Value
<code>pthread_setname_np()</code> , <code>pthread_getname_np()</code>	Thread safety	MT-Safe

CONFORMING TO

These functions are nonstandard GNU extensions.

NOTES

`pthread_setname_np()` internally writes to the thread-specific *comm* file under the `/proc` filesystem: `/proc/self/task/[tid]/comm`. `pthread_getname_np()` retrieves it from the same location.

EXAMPLE

The program below demonstrates the use of `pthread_setname_np()` and `pthread_getname_np()`.

The following shell session shows a sample run of the program:

```

$ ./a.out
Created a thread. Default name is: a.out
The thread name after setting it is THREADFOO.
^Z # Suspend the program
[1]+ Stopped ./a.out
$ ps H -C a.out -o 'pid tid cmd comm'
PID TID CMD COMMAND
5990 5990 ./a.out a.out
5990 5991 ./a.out THREADFOO
$ cat /proc/5990/task/5990/comm
a.out
$ cat /proc/5990/task/5991/comm
THREADFOO

```

Program source

```

#define _GNU_SOURCE
#include <pthread.h>
#include <stdio.h>
#include <string.h>
#include <unistd.h>
#include <errno.h>
#include <stdlib.h>

#define NAMELEN 16

#define errExitEN(en, msg) \
do { errno = en; perror(msg); exit(EXIT_FAILURE); \
} while (0)

static void *
threadfunc(void *parm)
{
sleep(5)
// allow main program to set the thread name
return NULL;
}

int
main(int argc, char **argv)
{
pthread_t thread;
int rc;
char thread_name[NAMELEN];

rc = pthread_create(&thread, NULL, threadfunc, NULL);
if (rc != 0)
errExitEN(rc, "pthread_create");

rc = pthread_getname_np(thread, thread_name, NAMELEN);
if (rc != 0)
errExitEN(rc, "pthread_getname_np");

printf("Created a thread. Default name is: %s\n", thread_name);
rc = pthread_setname_np(thread, (argc > 1) ? argv[1] : "THREADFOO");
if (rc != 0)
errExitEN(rc, "pthread_setname_np");

sleep(2)

```

```
rc = pthread_getname_np(thread, thread_name,  
(argc > 2) ? atoi(argv[1]) : NAMELEN);  
if (rc != 0)  
errExitEN(rc, "pthread_getname_np");  
printf("The thread name after setting it is %s.\n", thread_name);  
  
rc = pthread_join(thread, NULL);  
if (rc != 0)  
errExitEN(rc, "pthread_join");  
  
printf("Done\n");  
exit(EXIT_SUCCESS);  
}
```

SEE ALSO

[prctl\(2\)](#), [pthread_create\(3\)](#), [pthreads\(7\)](#)

COLOPHON

This page is part of release 4.10 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.