

NAME

`sem_destroy` - destroy an unnamed semaphore

SYNOPSIS

```
#include <semaphore.h>
```

```
int sem_destroy(sem_t *sem);
```

Link with `-pthread`.

DESCRIPTION

`sem_destroy()` destroys the unnamed semaphore at the address pointed to by `sem`.

Only a semaphore that has been initialized by `sem_init(3)` should be destroyed using `sem_destroy()`.

Destroying a semaphore that other processes or threads are currently blocked on (in `sem_wait(3)`) produces undefined behavior.

Using a semaphore that has been destroyed produces undefined results, until the semaphore has been reinitialized using `sem_init(3)`.

RETURN VALUE

`sem_destroy()` returns 0 on success; on error, -1 is returned, and `errno` is set to indicate the error.

ERRORS**EINVAL**

`sem` is not a valid semaphore.

ATTRIBUTES

For an explanation of the terms used in this section, see [attributes\(7\)](#).

Interface	Attribute	Value
<code>sem_destroy()</code>	Thread safety	MT-Safe

CONFORMING TO

POSIX.1-2001, POSIX.1-2008.

NOTES

An unnamed semaphore should be destroyed with `sem_destroy()` before the memory in which it is located is deallocated. Failure to do this can result in resource leaks on some implementations.

SEE ALSO

[sem_init\(3\)](#), [sem_post\(3\)](#), [sem_wait\(3\)](#), [sem_overview\(7\)](#)

COLOPHON

This page is part of release 4.10 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.