

**NAME**

tellmdir - return current location in directory stream

**SYNOPSIS**

```
#include <dirent.h>
```

```
long tellmdir(DIR *dirp);
```

Feature Test Macro Requirements for glibc (see [feature\\_test\\_macros\(7\)](#)):

```
telldir(): _XOPEN_SOURCE || /* Glibc since 2.19: */ _DEFAULT_SOURCE || /* Glibc versions <= 2.19: */
*_BSD_SOURCE || _SVID_SOURCE
```

**DESCRIPTION**

The **telldir()** function returns the current location associated with the directory stream *dirp*.

**RETURN VALUE**

On success, the **telldir()** function returns the current location in the directory stream. On error, -1 is returned, and *errno* is set appropriately.

**ERRORS****EBADF**

Invalid directory stream descriptor *dirp*.

**ATTRIBUTES**

For an explanation of the terms used in this section, see [attributes\(7\)](#).

Interface	Attribute	Value
telldir()	Thread safety	MT-Safe

**CONFORMING TO**

POSIX.1-2001, POSIX.1-2008, 4.3BSD.

**NOTES**

In glibc up to version 2.1.1, the return type of **telldir()** was *off\_t*. POSIX.1-2001 specifies *long*, and this is the type used since glibc 2.1.2.

In early filesystems, the value returned by **telldir()** was a simple file offset within a directory. Modern filesystems use tree or hash structures, rather than flat tables, to represent directories. On such filesystems, the value returned by **telldir()** (and used internally by [readdir\(3\)](#)) is a "cookie" that is used by the implementation to derive a position within a directory. Application programs should treat this strictly as an opaque value, making *no* assumptions about its contents.

**SEE ALSO**

[closedir\(3\)](#), [opendir\(3\)](#), [readdir\(3\)](#), [rewinddir\(3\)](#), [scandir\(3\)](#), [seekdir\(3\)](#)

**COLOPHON**

This page is part of release 4.10 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.