

**NAME**

Filter::Util::Call - Perl Source Filter Utility Module

**SYNOPSIS**

```
use Filter::Util::Call ;
```

**DESCRIPTION**

This module provides you with the framework to write *Source Filters* in Perl.

An alternate interface to [Filter::Util::Call](#) is now available. See [Filter::Simple](#) for more details.

A *Perl Source Filter* is implemented as a Perl module. The structure of the module can take one of two broadly similar formats. To distinguish between them, the first will be referred to as *method filter* and the second as *closure filter*.

Here is a skeleton for the *method filter*:

```
package MyFilter ;

use Filter::Util::Call ;

sub import
{
my($type, @arguments) = @_ ;
filter_add([]) ;
}

sub filter
{
my($self) = @_ ;
my($status) ;

$status = filter_read() ;
$status ;
}

1 ;
```

and this is the equivalent skeleton for the *closure filter*:

```
package MyFilter ;

use Filter::Util::Call ;

sub import
{
my($type, @arguments) = @_ ;

filter_add(
sub
{
my($status) ;
$status = filter_read() ;
$status ;
} )
}

1 ;
```

To make use of either of the two filter modules above, place the line below in a Perl source file.

```
use MyFilter;
```

In fact, the skeleton modules shown above are fully functional *Source Filters*, albeit fairly useless ones. All they does is filter the source stream without modifying it at all.

As you can see both modules have a broadly similar structure. They both make use of the `Filter::Util::Call` module and both have an `import` method. The difference between them is that the *method filter* requires a *filter* method, whereas the *closure filter* gets the equivalent of a *filter* method with the anonymous sub passed to `filter_add`.

To make proper use of the *closure filters* shown above you need to have a good understanding of the concept of a *closure*. See [perlref\(1\)](#) for more details on the mechanics of *closures*.

### use Filter::Util::Call

The following functions are exported by `Filter::Util::Call`

```
filter_add()
filter_read()
filter_read_exact()
filter_del()
```

### import()

The `import` method is used to create an instance of the filter. It is called indirectly by Perl when it encounters the `use MyFilter` line in a source file (See “import” in [perlfunc\(1\)](#) for more details on `import`).

It will always have at least one parameter automatically passed by Perl - this corresponds to the name of the package. In the example above it will be `"MyFilter"`.

Apart from the first parameter, `import` can accept an optional list of parameters. These can be used to pass parameters to the filter. For example:

```
use MyFilter qw(a b c) ;
```

will result in the `@_` array having the following values:

```
@_ [0] => "MyFilter"
@_ [1] => "a"
@_ [2] => "b"
@_ [3] => "c"
```

Before terminating, the `import` function must explicitly install the filter by calling `filter_add`.

### filter\_add()

The function, `filter_add`, actually installs the filter. It takes one parameter which should be a reference. The kind of reference used will dictate which of the two filter types will be used.

If a CODE reference is used then a *closure filter* will be assumed.

If a CODE reference is not used, a *method filter* will be assumed. In a *method filter*, the reference can be used to store context information. The reference will be *blessed* into the package by `filter_add`.

See the filters at the end of this documents for examples of using context information using both *method filters* and *closure filters*.

### filter() and anonymous sub

Both the `filter` method used with a *method filter* and the anonymous sub used with a *closure filter* is where the main processing for the filter is done.

The big difference between the two types of filter is that the *method filter* uses the object passed to the method to store any context data, whereas the *closure filter* uses the lexical variables that are maintained by the closure.

Note that the single parameter passed to the *method filter*, `$self`, is the same reference that was passed to `filter_add` blessed into the filter’s package. See the example filters later on for details

of using `$self`.

Here is a list of the common features of the anonymous sub and the `filter()` method.

**\$\_** Although `$_` doesn't actually appear explicitly in the sample filters above, it is implicitly used in a number of places.

Firstly, when either `filter` or the anonymous sub are called, a local copy of `$_` will automatically be created. It will always contain the empty string at this point.

Next, both `filter_read` and `filter_read_exact` will append any source data that is read to the end of `$_`.

Finally, when `filter` or the anonymous sub are finished processing, they are expected to return the filtered source using `$_`.

This implicit use of `$_` greatly simplifies the filter.

### **\$status**

The status value that is returned by the user's `filter` method or anonymous sub and the `filter_read` and `read_exact` functions take the same set of values, namely:

```
< 0 Error
= 0 EOF
> 0 OK
```

### **filter\_read** and **filter\_read\_exact**

These functions are used by the filter to obtain either a line or block from the next filter in the chain or the actual source file if there aren't any other filters.

The function `filter_read` takes two forms:

```
$status = filter_read() ;
$status = filter_read($size) ;
```

The first form is used to request a *line*, the second requests a *block*.

In line mode, `filter_read` will append the next source line to the end of the `$_` scalar.

In block mode, `filter_read` will append a block of data which is `<= $size` to the end of the `$_` scalar. It is important to emphasise that `filter_read` will not necessarily read a block which is *precisely* `$size` bytes.

If you need to be able to read a block which has an exact size, you can use the function `filter_read_exact`. It works identically to `filter_read` in block mode, except it will try to read a block which is exactly `$size` bytes in length. The only circumstances when it will not return a block which is `$size` bytes long is on EOF or error.

It is *very* important to check the value of `$status` after *every* call to `filter_read` or `filter_read_exact`.

### **filter\_del**

The function, `filter_del`, is used to disable the current filter. It does not affect the running of the filter. All it does is tell Perl not to call filter any more.

See "Example 4: Using `filter_del`" for details.

### *real\_import*

Internal function which adds the filter, based on the `filter_add` argument type.

## **EXAMPLES**

Here are a few examples which illustrate the key concepts - as such most of them are of little practical use.

The `examples` sub-directory has copies of all these filters implemented both as *method filters* and as *closure filters*.

**Example 1: A simple filter.**

Below is a *method filter* which is hard-wired to replace all occurrences of the string "Joe" to "Jim". Not particularly Useful, but it is the first example and I wanted to keep it simple.

```
package Joe2Jim ;

use Filter::Util::Call ;

sub import
{
my($type) = @_ ;

filter_add(bless []) ;
}

sub filter
{
my($self) = @_ ;
my($status) ;

s/Joe/Jim/g
if ($status = filter_read()) > 0 ;
$status ;
}

1 ;
```

Here is an example of using the filter:

```
use Joe2Jim ;
print "Where is Joe?\n" ;
```

And this is what the script above will print:

```
Where is Jim?
```

**Example 2: Using the context**

The previous example was not particularly useful. To make it more general purpose we will make use of the context data and allow any arbitrary *from* and *to* strings to be used. This time we will use a *closure filter*. To reflect its enhanced role, the filter is called **Subst**.

```
package Subst ;

use Filter::Util::Call ;
use Carp ;

sub import
{
croak("usage: use Subst qw(from to)")
unless @_ == 3 ;
my ($self, $from, $to) = @_ ;
filter_add(
sub
{
my ($status) ;
s/$from/$to/
if ($status = filter_read()) > 0 ;
$status ;
})
}
```

```

}
1 ;

```

and is used like this:

```

use Subst qw(Joe Jim) ;
print "Where is Joe?\n" ;

```

### Example 3: Using the context within the filter

Here is a filter which a variation of the `Joe2Jim` filter. As well as substituting all occurrences of "Joe" to "Jim" it keeps a count of the number of substitutions made in the context object.

Once EOF is detected (`$status` is zero) the filter will insert an extra line into the source stream. When this extra line is executed it will print a count of the number of substitutions actually made. Note that `$status` is set to 1 in this case.

```

package Count ;

use Filter::Util::Call ;

sub filter
{
my ($self) = @_ ;
my ($status) ;

if (($status = filter_read()) > 0 ) {
s/Joe/Jim/g ;
++ $$self ;
}
elsif ($$self >= 0) { # EOF
$_ = "print q[Made ${$self} substitutions\n]" ;
$status = 1 ;
$$self = -1 ;
}

$status ;
}

sub import
{
my ($self) = @_ ;
my ($count) = 0 ;
filter_add(\ $count) ;
}

1 ;

```

Here is a script which uses it:

```

use Count ;
print "Hello Joe\n" ;
print "Where is Joe\n" ;

```

Outputs:

```

Hello Jim
Where is Jim
Made 2 substitutions

```

**Example 4: Using filter\_del**

Another variation on a theme. This time we will modify the `Subst` filter to allow a starting and stopping pattern to be specified as well as the *from* and *to* patterns. If you know the *vi* editor, it is the equivalent of this command:

```
:/start/,/stop/s/from/to/
```

When used as a filter we want to invoke it like this:

```
use NewSubst qw(start stop from to) ;
```

Here is the module.

```
package NewSubst ;

use Filter::Util::Call ;
use Carp ;

sub import
{
my ($self, $start, $stop, $from, $to) = @_ ;
my ($found) = 0 ;
croak("usage: use Subst qw(start stop from to)")
unless @_ == 5 ;

filter_add(
sub
{
my ($status) ;

if (($status = filter_read()) > 0) {

$found = 1
if $found == 0 and /$start/ ;

if ($found) {
s/$from/$to/ ;
filter_del() if /$stop/ ;
}

}
$status ;
} )

}

1 ;
```

**Filter::Simple**

If you intend using the `Filter::Call` functionality, I would strongly recommend that you check out Damian Conway's excellent [Filter::Simple](#) module. Damian's module provides a much cleaner interface than `Filter::Util::Call`. Although it doesn't allow the fine control that `Filter::Util::Call` does, it should be adequate for the majority of applications. It's available at

<http://search.cpan.org/dist/Filter-Simple/>

**AUTHOR**

Paul Marquess

**DATE**

26th January 1996