

NAME

Locale::Codes::LangExt - standard codes for language extension identification

SYNOPSIS

```
use Locale::Codes::LangExt;

$lext = code2langext('acm'); # $lext gets 'Mesopotamian Arabic'
$code = langext2code('Mesopotamian Arabic'); # $code gets 'acm'

@codes = all_langext_codes();
@names = all_langext_names();
```

DESCRIPTION

The `Locale::Codes::LangExt` module provides access to standard codes used for identifying language extensions, such as those as defined in the IANA language registry.

Most of the routines take an optional additional argument which specifies the code set to use. If not specified, the default IANA language registry codes will be used.

SUPPORTED CODE SETS

There are several different code sets you can use for identifying language extensions. A code set may be specified using either a name, or a constant that is automatically exported by this module.

For example, the two are equivalent:

```
$lext = code2langext('acm','alpha');
$lext = code2langext('acm',LOCALE_LANGEXT_ALPHA);
```

The codesets currently supported are:

alpha

This is the set of three-letter (lowercase) codes from the IANA language registry, such as 'acm' for Mesopotamian Arabic.

This is the default code set.

ROUTINES

```
code2langext ( CODE [,CODESET] )
langext2code ( NAME [,CODESET] )
langext_code2code ( CODE ,CODESET ,CODESET2 )
all_langext_codes ( [CODESET] )
all_langext_names ( [CODESET] )
Locale::Codes::LangExt::rename_langext ( CODE ,NEW_NAME [,CODESET] )
Locale::Codes::LangExt::add_langext ( CODE ,NAME [,CODESET] )
Locale::Codes::LangExt::delete_langext ( CODE [,CODESET] )
Locale::Codes::LangExt::add_langext_alias ( NAME ,NEW_NAME )
Locale::Codes::LangExt::delete_langext_alias ( NAME )
Locale::Codes::LangExt::rename_langext_code ( CODE ,NEW_CODE [,CODESET] )
Locale::Codes::LangExt::add_langext_code_alias ( CODE ,NEW_CODE [,CODESET] )
Locale::Codes::LangExt::delete_langext_code_alias ( CODE [,CODESET] )
```

These routines are all documented in the `Locale::Codes::API` man page.

SEE ALSO

Locale::Codes

The Locale-Codes distribution.

Locale::Codes::API

The list of functions supported by this module.

<http://www.iana.org/assignments/language-subtag-registry> -P 4 The IANA language subtag registry.

AUTHOR

See [Locale::Codes](#) for full author history.

Currently maintained by Sullivan Beck (sbeck@cpan.org).

COPYRIGHT

Copyright (c) 2011-2014 Sullivan Beck

This module is free software; you can redistribute it and/or modify it under the same terms as Perl itself.