

**NAME**

Pod::Escapes - for resolving Pod E<...> sequences

**SYNOPSIS**

```
use Pod::Escapes qw(e2char);
...la la la, parsing POD, la la la...
$text = e2char($e_node->label);
unless(defined $text) {
    print "Unknown E sequence \"", $e_node->label, "\"!";
}
...else print/interpolate $text...
```

**DESCRIPTION**

This module provides things that are useful in decoding Pod E<...> sequences. Presumably, it should be used only by Pod parsers and/or formatters.

By default, `Pod::Escapes` exports none of its symbols. But you can request any of them to be exported. Either request them individually, as with `use Pod::Escapes qw(symbolname symbolname2...);`, or you can do `use Pod::Escapes qw(:ALL);` to get all exportable symbols.

**GOODIES**

`e2char($e_content)`

Given a name or number that could appear in a E<name\_or\_num> sequence, this returns the string that it stands for. For example, `e2char('sol')`, `e2char('47')`, `e2char('0x2F')`, and `e2char('057')` all return `"/`, because E<sol>, E<47>, E<0x2f>, and E<057>, all mean `"/`. If the name has no known value (as with a name of `"qacute"`) or is syntactically invalid (as with a name of `"1/4"`), this returns `undef`.

`e2charnum($e_content)`

Given a name or number that could appear in a E<name\_or\_num> sequence, this returns the number of the Unicode character that this stands for. For example, `e2char('sol')`, `e2char('47')`, `e2char('0x2F')`, and `e2char('057')` all return `47`, because E<sol>, E<47>, E<0x2f>, and E<057>, all mean `"/`, whose Unicode number is `47`. If the name has no known value (as with a name of `"qacute"`) or is syntactically invalid (as with a name of `"1/4"`), this returns `undef`.

`$Name2character{name}`

Maps from names (as in E<name>) like `"eacute"` or `"sol"` to the string that each stands for. Note that this does not include numerics (like `"64"` or `"x981c"`). Under old Perl versions (before 5.7) you get a `"?"` in place of characters whose Unicode value is over 255.

`$Name2character_number{name}`

Maps from names (as in E<name>) like `"eacute"` or `"sol"` to the Unicode value that each stands for. For example, `$Name2character_number{'eacute'}` is `201`, and `$Name2character_number{'eacute'}` is `8364`. You get the correct Unicode value, regardless of the version of Perl you're using — which differs from `%Name2character`'s behavior under pre-5.7 Perls.

Note that this hash does not include numerics (like `"64"` or `"x981c"`).

`$Latin1Code_to_fallback{integer}`

For numbers in the range 160 (0x00A0) to 255 (0x00FF), this maps from the character code for a Latin-1 character (like 233 for lowercase e-acute) to the US-ASCII character that best approximates it (like `"e"`). You may find this useful if you are rendering POD in a format that you think deals well only with US-ASCII characters.

`$Latin1Char_to_fallback{character}`

Just as above, but maps from characters (like `"\xE9"`, lowercase e-acute) to characters (like `"e"`).

`$Code2USASCII{integer}`

This maps from US-ASCII codes (like 32) to the corresponding character (like space, for 32). Only characters 32 to 126 are defined. This is meant for use by `e2char($x)` when it senses that it's running on a non-ASCII platform (where `chr(32)` doesn't get you a space — but `$Code2USASCII{32}` will). It's documented here just in case you might find it useful.

## CAVEATS

On Perl versions before 5.7, Unicode characters with a value over 255 (like lambda or emdash) can't be conveyed. This module does work under such early Perl versions, but in the place of each such character, you get a “?”. Latin-1 characters (characters 160-255) are unaffected.

Under EBCDIC platforms, `e2char($n)` may not always be the same as `chr(e2charnum($n))`, and ditto for `$Name2character{$name}` and `chr($Name2character_number{$name})`, because the strings are returned as native, and the numbers are returned as Unicode. However, for Perls starting with v5.8, `e2char($n)` is the same as `chr(utf8::unicode_to_native(e2charnum($n)))`, and ditto for `$Name2character{$name}` and `chr(utf8::unicode_to_native($Name2character_number{$name}))`.

## SEE ALSO

Pod::Browser - a pod web server based on Catalyst.

[Pod::Checker](#) - check pod documents for syntax errors.

Pod::Coverage - check if the documentation for a module is comprehensive.

[perlpod\(1\)](#) - description of pod format (for people documenting with pod).

[perlpodspec\(1\)](#) - specification of pod format (for people processing it).

Text::Unidecode - ASCII transliteration of Unicode text.

## REPOSITORY

<https://github.com/neilbowers/Pod-Escapes>

## COPYRIGHT AND DISCLAIMERS

Copyright (c) 2001-2004 Sean M. Burke. All rights reserved.

This library is free software; you can redistribute it and/or modify it under the same terms as Perl itself.

This program is distributed in the hope that it will be useful, but without any warranty; without even the implied warranty of merchantability or fitness for a particular purpose.

Portions of the data tables in this module are derived from the entity declarations in the W3C XHTML specification.

Currently (October 2001), that's these three:

<http://www.w3.org/TR/xhtml1/DTD/xhtml-lat1.ent>  
<http://www.w3.org/TR/xhtml1/DTD/xhtml-special.ent>  
<http://www.w3.org/TR/xhtml1/DTD/xhtml-symbol.ent>

## AUTHOR

Sean M. Burke [sburke@cpan.org](mailto:sburke@cpan.org)

Now being maintained by Neil Bowers [neilb@cpan.org](mailto:neilb@cpan.org)