

NAME

less - perl pragma to request less of something

SYNOPSIS

```
use less 'CPU';
```

DESCRIPTION

This is a user-pragma. If you're very lucky some code you're using will know that you asked for less CPU usage or ram or fat or... we just can't know. Consult your documentation on everything you're currently using.

For general suggestions, try requesting CPU or `memory`.

```
use less 'memory';
use less 'CPU';
use less 'fat';
```

If you ask for nothing in particular, you'll be asking for `less 'please'`.

```
use less 'please';
```

FOR MODULE AUTHORS

less has been in the core as a “joke” module for ages now and it hasn't had any real way to communicating any information to anything. Thanks to Nicholas Clark we have user pragmas (see `perlpragma`) and now `less` can do something.

You can probably expect your users to be able to guess that they can request less CPU or memory or just “less” overall.

If the user didn't specify anything, it's interpreted as having used the `please` tag. It's up to you to make this useful.

```
# equivalent
use less;
use less 'please';
```

```
BOOLEAN = less->of( FEATURE )
```

The class method `less->of(NAME)` returns a boolean to tell you whether your user requested less of something.

```
if ( less->of( 'CPU' ) ) {
    ...
}
elsif ( less->of( 'memory' ) ) {

}
}
```

```
FEATURES = less->of()
```

If you don't ask for any feature, you get the list of features that the user requested you to be nice to. This has the nice side effect that if you don't respect anything in particular then you can just ask for it and use it like a boolean.

```
if ( less->of ) {
    ...
}
else {
    ...
}
```

CAVEATS

This probably does nothing.

This works only on 5.10+

At least it's backwards compatible in not doing much.