

NAME

AptPkg::Cache - APT package cache interface

SYNOPSIS

```
use AptPkg::Cache;
```

DESCRIPTION

The AptPkg::Cache module provides an interface to **APT**'s package cache.

AptPkg::Cache

The AptPkg::Cache package implements the **APT** pkgCacheFile class as a hash reference (inherits from AptPkg::hash). The hash keys are the names of packages in the cache, and the values are AptPkg::Cache::Package objects (which in turn appear as hash references, see below).

Constructor

```
new([LOCK])
```

Instantiation of the object uses configuration from the `$AptPkg::Config::_config` and `$AptPkg::System::_system` objects (automatically initialised if not done explicitly).

The cache initialisation can be quite verbose — controlled by the value of `$_config->{quiet}`, which is set to “2” (quiet) if the `$_config` object is auto-initialised.

The cache directory is locked if `LOCK` is true.

It is important to note that the structure of the returned object contains self-referential elements, so some care must be taken if attempting to traverse it recursively.

*Methods**files*

Return a list of AptPkg::Cache::PkgFile objects describing the package files.

packages

Return an AptPkg::PkgRecords object which may be used to retrieve additional information about packages.

get, exists, keys

These methods are used to implement the hashref abstraction: `$obj->get($pack)` and `$obj->{$pack}` are equivalent.

is_multi_arch

Cache is multi-arch enabled.

native_arch

Native architecture.

AptPkg::Cache::Package

Implements the **APT** pkgCache::PkgIterator class as a hash reference.

*Keys**Name**Section**Arch*

Package name, section and architecture.

FullName

Fully qualified name, including architecture.

ShortName

The shortest unambiguous package name: the same as `Name` for native packages, and `FullName` for non-native.

SelectedState

InstState

CurrentState

Package state from the status file.

SelectedState may be **Unknown**, **Install**, **Hold**, **DeInstall** or **Purge**.

InstState may be **Ok**, **ReInstReq**, **HoldInst** or **HoldReInstReq**.

CurrentState may be **NotInstalled**, **UnPacked**, **HalfConfigured**, **HalfInstalled**, **ConfigFiles** or **Installed**.

In a numeric context, SelectedState, InstState and CurrentState evaluate to an AptPkg::State:: constant.

VersionList

A reference to an array of AptPkg::Cache::Version objects describing available versions of the package.

CurrentVer

An AptPkg::Cache::Version object describing the currently installed version (if any) of the package.

RevDependsList

A reference to an array of AptPkg::Cache::Depends objects describing packages which depend upon the current package.

ProvidesList

For virtual packages, this is a reference to an array of AptPkg::Cache::Provides objects describing packages which provide the current package.

Flags

A comma separated list of flags: **Auto**, **Essential** or **Important**.

In a numeric context, evaluates to a combination of AptPkg::Flag:: constants.

[Note: the only one of these you need worry about is **Essential**, which is set based on the package's header of the same name. **Auto** seems to be used internally by **APT**, and **Important** seems to only be set on the apt package.]

Index

Internal **APT** unique reference for the package record.

AptPkg::Cache::Version

Implements the **APT** pkgCache::VerIterator class as a hash reference.

Keys

VerStr

Section

Arch

The package version, section and architecture.

MultiArch

Multi-arch state: **None**, **All**, **Foreign**, **Same**, **Allowed**, **AllForeign** or **AllAllowed**.

In a numeric context, evaluates to an AptPkg::Version:: constant.

ParentPkg

An AptPkg::Cache::Package object describing the package providing this version.

DescriptionList

A list of AptCache::Cache::Description objects describing the files which describe a package version. The list includes both Package files and Translation files, which contain translated Description fields.

TranslatedDescription

An AptCache::Cache::Description object for the current locale, which will generally be a Translation file.

DependsList

A reference to an array of AptPkg::Cache::Depends objects describing packages which the current package depends upon.

ProvidesList

A reference to an array of AptPkg::Cache::Provides objects describing virtual packages provided by this version.

FileList

A reference to an array of AptPkg::Cache::VerFile objects describing the packages files which include the current version.

Size

The *.deb* file size, in bytes.

InstalledSize

The disk space used when installed, in bytes.

Index

Internal **APT** unique reference for the version record.

Priority

Package priority: **important**, **required**, **standard**, **optional** or **extra**.

In a numeric context, evaluates to an AptPkg::VerPriority:: constant.

AptPkg::Cache::Depends

Implements the **APT** pkgCache::DepIterator class as a hash reference.

*Keys***DepType**

Type of dependency: **Depends**, **PreDepends**, **Suggests**, **Recommends**, **Conflicts**, **Replaces** or **Obsoletes**.

In a numeric context, evaluates to an AptPkg::Dep:: constant.

ParentPkg**ParentVer**

AptPkg::Cache::Package and AptPkg::Cache::Version objects describing the package declaring the dependency.

TargetPkg

AptPkg::Cache::Package object describing the depended package.

TargetVer

For versioned dependencies, TargetVer is a string giving the version of the target package required.

CompType**CompTypeDeb**

CompType gives a normalised comparison operator (>, >=, etc) describing the relationship to TargetVer (if none).

CompTypeDeb returns Debian-style operators (>> rather than >).

In a numeric context, both CompType and CompTypeDeb evaluate to an AptPkg::Dep:: constant.

Alternative dependencies (Depends: a | b) are identified by all but the last having the AptPkg::Dep::Or bit set in the numeric representation of CompType (and CompTypeDeb).

Index

Internal **APT** unique reference for the dependency record.

AptPkg::Cache::Provides

Implements the **APT** `pkgCache::PrvIterator` class as a hash reference.

*Keys***Name**

Name of virtual package.

OwnerPkg**OwnerVer**

`AptPkg::Cache::Package` and `AptPkg::Cache::Version` objects describing the providing package.

ProvideVersion

Version of the virtual package. [Not currently supported by `dpkg`]

Index

Internal **APT** unique reference for the provides record.

AptPkg::Cache::VerFile

Implements the **APT** `pkgCache::VerFileIterator` class as a hash reference.

*Keys***File**

An `AptPkg::Cache::PkgFile` object describing the packages file.

Offset**Size**

The byte offset and length of the entry in the file.

Index

Internal **APT** unique reference for the version file record.

AptPkg::Cache::PkgFile

Implements the **APT** `pkgCache::PkgFileIterator` class as a hash reference.

*Keys***FileName**

Packages file path.

IndexType

File type: `Debian Package Index`, `Debian dpkg status file`.

Archive**Component****Version****Origin****Label****Site**

Fields from the Release file.

IsOk

True if the cache is in sync with this file.

Index

Internal **APT** unique reference for the package file record.

AptPkg::Cache::DescFile

Implements the **APT** `pkgCache::DescFileIterator` class as a hash reference.

Keys

File

An AptPkg::Cache::PkgFile object describing the packages file.

SEE ALSO

AptPkg::Config (3pm), *AptPkg::System* (3pm), *AptPkg* (3pm), *AptPkg::hash* (3pm),
AptPkg::PkgRecords (3pm), *AptPkg::Policy* (3pm).

AUTHOR

Brendan O'Dea <bod@debian.org>