

NAME

Log::Message::Item - Message objects for Log::Message

SYNOPSIS

```
# Implicitly used by Log::Message to create Log::Message::Item objects

print "this is the message's id: ", $item->id;

print "this is the message stored: ", $item->message;

print "this is when it happened: ", $item->when;

print "the message was tagged: ", $item->tag;

print "this was the severity level: ", $item->level;

$item->remove; # delete the item from the stack it was on

# Besides these methods, you can also call the handlers on
# the object specifically.
# See the Log::Message::Handlers manpage for documentation on what
# handlers are available by default and how to add your own
```

DESCRIPTION

[Log::Message::Item](#) is a class that generates generic Log items. These items are stored on a [Log::Message](#) stack, so see the [Log::Message](#) manpage about details how to retrieve them.

You should probably not create new items by yourself, but use the storing mechanism provided by [Log::Message](#).

However, the accessors and handlers are of interest if you want to do fine tuning of how your messages are handled.

The accessors and methods are described below, the handlers are documented in the [Log::Message::Handlers](#) manpage.

Methods and Accessors

remove

Calling remove will remove the object from the stack it was on, so it will not show up any more in subsequent fetches of messages.

You can still call accessors and handlers on it however, to handle it as you will.

id

Returns the internal ID of the item. This may be useful for comparing since the ID is incremented each time a new item is created. Therefore, an item with ID 4 must have been logged before an item with ID 9.

when

Returns the timestamp of when the message was logged

message

The actual message that was stored

level

The severity type of this message, as well as the name of the handler that was called upon storing it.

tag

Returns the identification tag that was put on the message.

shortmess

Returns the equivalent of a `Carp::shortmess` for this item. See the `Carp` manpage for details.

longmess

Returns the equivalent of a `Carp::longmess` for this item, which is essentially a stack trace. See the `Carp` manpage for details.

parent

Returns a reference to the [Log::Message](#) object that stored this item. This is useful if you want to have access to the full stack in a handler.

SEE ALSO

[Log::Message](#), [Log::Message::Handlers](#), [Log::Message::Config](#)

AUTHOR

This module by Jos Boumans <kane@cpan.org>.

Acknowledgements

Thanks to Ann Barcomb for her suggestions.

COPYRIGHT

This module is copyright (c) 2002 Jos Boumans <kane@cpan.org>. All rights reserved.

This library is free software; you may redistribute and/or modify it under the same terms as Perl itself.