

NAME

Net::UPnP::QueryResponse - Perl extension for UPnP.

SYNOPSIS

```
use Net::UPnP::ControlPoint;

my $obj = Net::UPnP::ControlPoint->new();

@dev_list = $obj->search(st =>'upnp:rootdevice', mx => 3);

$devNum= 0;
foreach $dev (@dev_list) {
    $device_type = $dev->getdevicetype();
    if ($device_type ne 'urn:schemas-upnp-org:device:MediaServer:1') {
        next;
    }
    print "[ $devNum ] : " . $dev->getfriendlyname() . "\n";
    unless ($dev->getservicebyname('urn:schemas-upnp-org:service:ContentDirectory:1')) {
        next;
    }
    $condir_service = $dev->getservicebyname('urn:schemas-upnp-org:service:ContentDirectory:1');
    unless (defined($condir_service)) {
        next;
    }
    %action_in_arg = (
        'ObjectID' => 0,
        'BrowseFlag' => 'BrowseDirectChildren',
        'Filter' => '*',
        'StartingIndex' => 0,
        'RequestedCount' => 0,
        'SortCriteria' => '',
    );
    $action_res = $condir_service->postcontrol('Browse', \%action_in_arg);
    unless ($action_res->getstatusCode() == 200) {
        next;
    }
    $action_out_arg = $action_res->getargumentlist();
    unless ($action_out_arg->{'Result'}) {
        next;
    }
    $result = $action_out_arg->{'Result'};
    while ($result = m/<dc:title>(.*?)</dc:title>/sgi) {
        print "\t$1\n";
    }
    $devNum++;
}
```

DESCRIPTION

The package is used a object of the action response.

METHODS

getstatusCode - get the status code.

```
$status_code = $queryres->getstatusCode();
```

Get the status code of the SOAP response.

getvalue - get the return value.

```
$value = $queryres->getvalue();
```

Get the value of the SOAP response.

AUTHOR

Satoshi Konno skonno@cybergarage.org

CyberGarage <http://www.cybergarage.org>

COPYRIGHT AND LICENSE

Copyright (C) 2005 by Satoshi Konno

It may be used, redistributed, and/or modified under the terms of BSD License.