

NAME

ASN1_generate_nconf, ASN1_generate_v3 - ASN1 generation functions

SYNOPSIS

```
#include <openssl/asn1.h>
```

```
ASN1_TYPE *ASN1_generate_nconf(char *str, CONF *nconf);
ASN1_TYPE *ASN1_generate_v3(char *str, X509V3_CTX *cnf);
```

DESCRIPTION

These functions generate the ASN1 encoding of a string in an **ASN1_TYPE** structure.

str contains the string to encode **nconf** or **cnf** contains the optional configuration information where additional strings will be read from. **nconf** will typically come from a config file whereas **cnf** is obtained from an **X509V3_CTX** structure which will typically be used by X509 v3 certificate extension functions. **cnf** or **nconf** can be set to **NULL** if no additional configuration will be used.

GENERATION STRING FORMAT

The actual data encoded is determined by the string **str** and the configuration information. The general format of the string is:

```
[modifier,]type[:value]
```

That is zero or more comma separated modifiers followed by a type followed by an optional colon and a value. The formats of **type**, **value** and **modifier** are explained below.

SUPPORTED TYPES

The supported types are listed below. Unless otherwise specified only the **ASCII** format is permissible.

BOOLEAN, BOOL

This encodes a boolean type. The **value** string is mandatory and should be **TRUE** or **FALSE**. Additionally **TRUE**, **true**, **Y**, **y**, **YES**, **yes**, **FALSE**, **false**, **N**, **n**, **NO** and **no** are acceptable.

NULL

Encode the **NULL** type, the **value** string must not be present.

INTEGER, INT

Encodes an ASN1**INTEGER** type. The **value** string represents the value of the integer, it can be prefaced by a minus sign and is normally interpreted as a decimal value unless the prefix **0x** is included.

ENUMERATED, ENUM

Encodes the ASN1**ENUMERATED** type, it is otherwise identical to **INTEGER**.

OBJECT, OID

Encodes an ASN1**OBJECT IDENTIFIER**, the **value** string can be a short name, a long name or numerical format.

UTCTIME, UTC

Encodes an ASN1 **UTCTime** structure, the value should be in the format **YYMMDDHHMMSSZ**.

GENERALIZEDTIME, GENTIME

Encodes an ASN1 **GeneralizedTime** structure, the value should be in the format **YYYYMMDDHHMMSSZ**.

OCTETSTRING, OCT

Encodes an ASN1**OCTET STRING**. **value** represents the contents of this structure, the format strings **ASCII** and **HEX** can be used to specify the format of **value**.

BITSTRING, BITSTR

Encodes an ASN1BIT STRING. **value** represents the contents of this structure, the format strings **ASCII**, **HEX** and **BITLIST** can be used to specify the format of **value**.

If the format is anything other than **BITLIST** the number of unused bits is set to zero.

UNIVERSALSTRING, UNIV, IA5, IA5STRING, UTF8, UTF8String, BMP, BMPSTRING, VISIBLESTRING, VISIBLE, PRINTABLESTRING, PRINTABLE, T61, T61STRING, TELETEXSTRING, GeneralString, NUMERICSTRING, NUMERIC

These encode the corresponding string types. **value** represents the contents of this structure. The format can be **ASCII** or **UTF8**.

SEQUENCE, SEQ, SET

Formats the result as an ASN1SEQUENCE or SET type. **value** should be a section name which will contain the contents. The field names in the section are ignored and the values are in the generated string format. If **value** is absent then an empty SEQUENCE will be encoded.

MODIFIERS

Modifiers affect the following structure, they can be used to add EXPLICIT or IMPLICIT tagging, add wrappers or to change the string format of the final type and value. The supported formats are documented below.

EXPLICIT, EXP

Add an explicit tag to the following structure. This string should be followed by a colon and the tag value to use as a decimal value.

By following the number with **U**, **A**, **P** or **C** UNIVERSAL, APPLICATION, PRIVATE or CONTEXT SPECIFIC tagging can be used, the default is CONTEXT SPECIFIC.

IMPLICIT, IMP

This is the same as **EXPLICIT** except IMPLICIT tagging is used instead.

OCTWRAP, SEQWRAP, SETWRAP, BITWRAP

The following structure is surrounded by an OCTET STRING, a SEQUENCE, a SET or a BIT STRING respectively. For a BIT STRING the number of unused bits is set to zero.

FORMAT

This specifies the format of the ultimate value. It should be followed by a colon and one of the strings **ASCII**, **UTF8**, **HEX** or **BITLIST**.

If no format specifier is included then **ASCII** is used. If **UTF8** is specified then the value string must be a valid **UTF8** string. For **HEX** the output must be a set of hex digits. **BITLIST** (which is only valid for a BIT STRING) is a comma separated list of the indices of the set bits, all other bits are zero.

EXAMPLES

A simple IA5String:

```
IA5STRING:Hello World
```

An IA5String explicitly tagged:

```
EXPLICIT:0,IA5STRING:Hello World
```

An IA5String explicitly tagged using APPLICATION tagging:

```
EXPLICIT:0A,IA5STRING:Hello World
```

A BITSTRING with bits 1 and 5 set and all others zero:

```
FORMAT:BITLIST,BITSTRING:1,5
```

A more complex example using a config file to produce a SEQUENCE consisting of a BOOL an OID and a UTF8String:

```
asn1 = SEQUENCE:seq_section
```

```
[seq_section]
```

```
field1 = BOOLEAN:TRUE
```

```
field2 = OID:commonName
```

```
field3 = UTF8:Third field
```

This example produces an RSAPrivateKey structure, this is the key contained in the file client.pem in all OpenSSL distributions (note: the field names such as 'coeff' are ignored and are present just for clarity):

```
asn1=SEQUENCE:private_key
```

```
[private_key]
```

```
version=INTEGER:0
```

```
n=INTEGER:0xBB6FE79432CC6EA2D8F970675A5A87BFBE1AFF0BE63E879F2AFFB93644\
D4D2C6D000430DEC66ABF47829E74B8C5108623A1C0EE8BE217B3AD8D36D5EB4FCA1D9
```

```
e=INTEGER:0x010001
```

```
d=INTEGER:0x6F05EAD2F27FFAEC84BEC360C4B928FD5F3A9865D0FCAAD291E2A52F4A\
F810DC6373278C006A0ABBA27DC8C63BF97F7E666E27C5284D7D3B1FFFE16B7A87B51D
```

```
p=INTEGER:0xF3929B9435608F8A22C208D86795271D54EBDFB09DDEF539AB083DA912\
D4BD57
```

```
q=INTEGER:0xC50016F89DFF2561347ED1186A46E150E28BF2D0F539A1594BBD7FE467\
46EC4F
```

```
exp1=INTEGER:0x9E7D4326C924AFC1DEA40B45650134966D6F9DFA3A7F9D698CD4ABEA\
9COA39B9
```

```
exp2=INTEGER:0xBA84003BB95355AFB7C50DF140C60513D0BA51D637272E355E397779\
E7B2458F
```

```
coeff=INTEGER:0x30B9E4F2AFA5AC679F920FC83F1F2DF1BAF1779CF989447FABC2F5\
628657053A
```

This example is the corresponding public key in a SubjectPublicKeyInfo structure:

```
# Start with a SEQUENCE
```

```
asn1=SEQUENCE:pubkeyinfo
```

```
# pubkeyinfo contains an algorithm identifier and the public key wrapped
```

```
# in a BIT STRING
```

```
[pubkeyinfo]
```

```
algorithm=SEQUENCE:rsa_alg
```

```
pubkey=BITWRAP,SEQUENCE:rsapubkey
```

```
# algorithm ID for RSA is just an OID and a NULL
```

```
[rsa_alg]
```

```
algorithm=OID:rsaEncryption
```

```
parameter=NULL
```

```
# Actual public key: modulus and exponent
```

```
[rsapubkey]
```

```
n=INTEGER:0xBB6FE79432CC6EA2D8F970675A5A87BFBE1AFF0BE63E879F2AFFB93644\  
D4D2C6D000430DEC66ABF47829E74B8C5108623A1C0EE8BE217B3AD8D36D5EB4FCA1D9
```

```
e=INTEGER:0x010001
```

RETURN VALUES

ASN1_generate_nconf() and *ASN1_generate_v3()* return the encoded data as an **ASN1_TYPE** structure or **NULL** if an error occurred.

The error codes that can be obtained by *ERR_get_error(3)*.

SEE ALSO

[ERR_get_error\(3\)](#)

HISTORY

ASN1_generate_nconf() and *ASN1_generate_v3()* were added to OpenSSL 0.9.8