

NAME

`BN_set_bit`, `BN_clear_bit`, `BN_is_bit_set`, `BN_mask_bits`, `BN_lshift`, `BN_lshift1`, `BN_rshift`, `BN_rshift1` - bit operations on BIGNUMs

SYNOPSIS

```
#include <openssl/bn.h>

int BN_set_bit(BIGNUM *a, int n);
int BN_clear_bit(BIGNUM *a, int n);

int BN_is_bit_set(const BIGNUM *a, int n);

int BN_mask_bits(BIGNUM *a, int n);

int BN_lshift(BIGNUM *r, const BIGNUM *a, int n);
int BN_lshift1(BIGNUM *r, BIGNUM *a);

int BN_rshift(BIGNUM *r, BIGNUM *a, int n);
int BN_rshift1(BIGNUM *r, BIGNUM *a);
```

DESCRIPTION

`BN_set_bit()` sets bit **n** in **a** to 1 ($a |= (1 << n)$). The number is expanded if necessary.

`BN_clear_bit()` sets bit **n** in **a** to 0 ($a &= (1 << n)$). An error occurs if **a** is shorter than **n** bits.

`BN_is_bit_set()` tests if bit **n** in **a** is set.

`BN_mask_bits()` truncates **a** to an **n** bit number ($a &= ((0) >> n)$). An error occurs if **a** already is shorter than **n** bits.

`BN_lshift()` shifts **a** left by **n** bits and places the result in **r** ($r = a * 2^n$). `BN_lshift1()` shifts **a** left by one and places the result in **r** ($r = 2 * a$).

`BN_rshift()` shifts **a** right by **n** bits and places the result in **r** ($r = a / 2^n$). `BN_rshift1()` shifts **a** right by one and places the result in **r** ($r = a / 2$).

For the shift functions, **r** and **a** may be the same variable.

RETURN VALUES

`BN_is_bit_set()` returns 1 if the bit is set, 0 otherwise.

All other functions return 1 for success, 0 on error. The error codes can be obtained by [`ERR_get_error\(3\)`](#).

SEE ALSO

[`bn\(3\)`](#), [`BN_num_bytes\(3\)`](#), [`BN_add\(3\)`](#)

HISTORY

`BN_set_bit()`, `BN_clear_bit()`, `BN_is_bit_set()`, `BN_mask_bits()`, `BN_lshift()`, `BN_lshift1()`, `BN_rshift()`, and `BN_rshift1()` are available in all versions of SSLeay and OpenSSL.