

NAME

SSL_CONF_CTX_new, SSL_CONF_CTX_free - SSL configuration allocation functions

SYNOPSIS

```
#include <openssl/ssl.h>

SSL_CONF_CTX *SSL_CONF_CTX_new(void);
void SSL_CONF_CTX_free(SSL_CONF_CTX *cctx);
```

DESCRIPTION

The function *SSL_CONF_CTX_new()* allocates and initialises an **SSL_CONF_CTX** structure for use with the **SSL_CONF** functions.

The function *SSL_CONF_CTX_free()* frees up the context **cctx**. If **cctx** is **NULL** nothing is done.

RETURN VALUES

SSL_CONF_CTX_new() returns either the newly allocated **SSL_CONF_CTX** structure or **NULL** if an error occurs.

SSL_CONF_CTX_free() does not return a value.

SEE ALSO

[SSL_CONF_CTX_set_flags\(3\)](#), [SSL_CONF_CTX_set_ssl_ctx\(3\)](#), [SSL_CONF_CTX_set1_prefix\(3\)](#), [SSL_CONF_cmd\(3\)](#), [SSL_CONF_cmd_argv\(3\)](#)

HISTORY

These functions were first added to OpenSSL 1.0.2

COPYRIGHT

Copyright 2012-2016 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the OpenSSL license (the “License”). You may not use this file except in compliance with the License. You can obtain a copy in the file **LICENSE** in the source distribution or at <https://www.openssl.org/source/license.html>.