

NAME

SSL_SESSION_set_ex_data, SSL_SESSION_get_ex_data - get and set application specific data on a session

SYNOPSIS

```
#include <openssl/ssl.h>

int SSL_SESSION_set_ex_data(SSL_SESSION *ss, int idx, void *data);
void *SSL_SESSION_get_ex_data(const SSL_SESSION *s, int idx);
```

DESCRIPTION

SSL_SESSION_set_ex_data() enables an application to store arbitrary application specific data **data** in an SSL_SESSION structure **ss**. The index **idx** should be a value previously returned from a call to [CRYPTO_get_ex_new_index\(3\)](#).

SSL_SESSION_get_ex_data() retrieves application specific data previously stored in an SSL_SESSION structure **s**. The **idx** value should be the same as that used when originally storing the data.

RETURN VALUES

SSL_SESSION_set_ex_data() returns 1 for success or 0 for failure.

SSL_SESSION_get_ex_data() returns the previously stored value or NULL on failure. NULL may also be a valid value.

SEE ALSO

[ssl\(3\)](#), [CRYPTO_get_ex_new_index\(3\)](#)

COPYRIGHT

Copyright 2017 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the OpenSSL license (the “License”). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.