

**NAME**

SSL\_CTX\_ctrl, SSL\_CTX\_callback\_ctrl, SSL\_ctrl, SSL\_callback\_ctrl - internal handling functions for SSL\_CTX and SSL objects

**SYNOPSIS**

```
#include <openssl/ssl.h>

long SSL_CTX_ctrl(SSL_CTX *ctx, int cmd, long larg, void *parg);
long SSL_CTX_callback_ctrl(SSL_CTX *, int cmd, void (*fp)());

long SSL_ctrl(SSL *ssl, int cmd, long larg, void *parg);
long SSL_callback_ctrl(SSL *, int cmd, void (*fp)());
```

**DESCRIPTION**

The `SSL*_ctrl()` family of functions is used to manipulate settings of the SSL\_CTX and SSL objects. Depending on the command **cmd** the arguments **larg**, **parg**, or **fp** are evaluated. These functions should never be called directly. All functionalities needed are made available via other functions or macros.

**RETURN VALUES**

The return values of the `SSL*_ctrl()` functions depend on the command supplied via the **cmd** parameter.

**SEE ALSO**

*ssl(3)*

**COPYRIGHT**

Copyright 2001-2016 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the OpenSSL license (the “License”). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.