

NAME

SSL_get_psk_identity, SSL_get_psk_identity_hint - get PSK client identity and hint

SYNOPSIS

```
#include <openssl/ssl.h>

const char *SSL_get_psk_identity_hint(const SSL *ssl);
const char *SSL_get_psk_identity(const SSL *ssl);
```

DESCRIPTION

SSL_get_psk_identity_hint() is used to retrieve the PSK identity hint used during the connection setup related to SSL object **ssl**. Similarly, *SSL_get_psk_identity()* is used to retrieve the PSK identity used during the connection setup.

RETURN VALUES

If non-NULL, *SSL_get_psk_identity_hint()* returns the PSK identity hint and *SSL_get_psk_identity()* returns the PSK identity. Both are NULL-terminated. *SSL_get_psk_identity_hint()* may return NULL if no PSK identity hint was used during the connection setup.

Note that the return value is valid only during the lifetime of the SSL object **ssl**.

COPYRIGHT

Copyright 2006-2016 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the OpenSSL license (the “License”). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.

Copyright 2005 Nokia.