NAME

    complex - basics of complex mathematics

SYNOPSIS

    #include <complex.h>

DESCRIPTION

    Complex numbers are numbers of the form z = a+b*i, where a and b are real numbers and i = sqrt(-1), so that i*i = -1.

    There are other ways to represent that number. The pair (a,b) of real numbers may be viewed as a point in the plane, given by X- and Y-coordinates. This same point may also be described by giving the pair of real numbers (r,phi), where r is the distance to the origin O, and phi the angle between the X-axis and the line Oz. Now z = r*exp(i*phi) = r*(cos(phi)+i*sin(phi)).

    The basic operations are defined on z = a+b*i and w = c+d*i as:

    addition: z+w = (a+c) + (b+d)*i

    multiplication: z*w = (a*c - b*d) + (a*d + b*c)*i

    division: z/w = ((a*c + b*d)/(c*c + d*d)) + ((b*c - a*d)/(c*c + d*d))*i

    Nearly all math function have a complex counterpart but there are some complex-only functions.

EXAMPLE

    Your C-compiler can work with complex numbers if it supports the C99 standard. Link with *-lm*. The imaginary unit is represented by I.

    ```
    /* check that exp(i * pi) == -1 */
    #include <math.h> /* for atan */
    #include <stdio.h>
    #include <complex.h>

    int
    main(void)
    {
    double pi = 4 * atan(1.0);
    double complex z = cexp(I * pi);
    printf(%f + %f * in, creal(z), cimag(z));
    }
    ```

SEE ALSO

    cabs(3), cacos(3), cacosh(3), carg(3), casin(3), casinh(3), catan(3), catanh(3), ccos(3), ccosh(3), **cerf(3),** cexp(3), cexp2(3), cimag(3), clog(3), clog10(3), clog2(3), conj(3), cpow(3), cproj(3), creal(3), csin(3), csinh(3), csqrt(3), ctan(3), ctanh(3)

COLOPHON

    This page is part of release 3.74 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at http://www.kernel.org/doc/man-pages/.