

NAME

gitglossary - A Git Glossary

SYNOPSIS

*

DESCRIPTION

alternate object database

Via the alternates mechanism, a repository can inherit part of its object database from another object database, which is called an alternate.

bare repository

A bare repository is normally an appropriately named directory with a `.git` suffix that does not have a locally checked-out copy of any of the files under revision control. That is, all of the Git administrative and control files that would normally be present in the hidden `.git` sub-directory are directly present in the `repository.git` directory instead, and no other files are present and checked out. Usually publishers of public repositories make bare repositories available.

blob object

Untyped object, e.g. the contents of a file.

branch

A branch is an active line of development. The most recent commit on a branch is referred to as the tip of that branch. The tip of the branch is referenced by a branch head, which moves forward as additional development is done on the branch. A single Git repository can track an arbitrary number of branches, but your working tree is associated with just one of them (the current or checked out branch), and `HEAD` points to that branch.

cache

Obsolete for: `index`.

chain

A list of objects, where each object in the list contains a reference to its successor (for example, the successor of a commit could be one of its parents).

changeset

`BitKeeper/cvsps` speak for commit. Since Git does not store changes, but states, it really does not make sense to use the term changesets with Git.

checkout

The action of updating all or part of the working tree with a tree object or blob from the object database, and updating the `index` and `HEAD` if the whole working tree has been pointed at a new branch.

cherry-picking

In SCM jargon, cherry pick means to choose a subset of changes out of a series of changes (typically commits) and record them as a new series of changes on top of a different codebase. In Git, this is performed by the `git cherry-pick` command to extract the change introduced by an existing commit and to record it based on the tip of the current branch as a new commit.

clean

A working tree is clean, if it corresponds to the revision referenced by the current head. Also see `dirty`.

commit

As a noun: A single point in the Git history; the entire history of a project is represented as a set of interrelated commits. The word commit is often used by Git in the same places other revision control systems use the words revision or version. Also used as a short hand for commit object.

As a verb: The action of storing a new snapshot of the project's state in the Git history, by creating a new commit representing the current state of the index and advancing HEAD to point at the new commit.

commit object

An object which contains the information about a particular revision, such as parents, committer, author, date and the tree object which corresponds to the top directory of the stored revision.

commit-ish (also committish)

A commit object or an object that can be recursively dereferenced to a commit object. The following are all commit-ishes: a commit object, a tag object that points to a commit object, a tag object that points to a tag object that points to a commit object, etc.

core Git

Fundamental data structures and utilities of Git. Exposes only limited source code management tools.

DAG

Directed acyclic graph. The commit objects form a directed acyclic graph, because they have parents (directed), and the graph of commit objects is acyclic (there is no chain which begins and ends with the same object).

dangling object

An unreachable object which is not reachable even from other unreachable objects; a dangling object has no references to it from any reference or object in the repository.

detached HEAD

Normally the HEAD stores the name of a branch, and commands that operate on the history HEAD represents operate on the history leading to the tip of the branch the HEAD points at. However, Git also allows you to check out an arbitrary commit that isn't necessarily the tip of any particular branch. The HEAD in such a state is called detached.

Note that commands that operate on the history of the current branch (e.g. `git commit` to build a new history on top of it) still work while the HEAD is detached. They update the HEAD to point at the tip of the updated history without affecting any branch. Commands that update or inquire information *about* the current branch (e.g. `git branch --set-upstream-to` that sets what remote-tracking branch the current branch integrates with) obviously do not work, as there is no (real) current branch to ask about in this state.

directory

The list you get with `ls :-)`

dirty

A working tree is said to be dirty if it contains modifications which have not been committed to the current branch.

evil merge

An evil merge is a merge that introduces changes that do not appear in any parent.

fast-forward

A fast-forward is a special type of merge where you have a revision and you are merging another branches changes that happen to be a descendant of what you have. In such these cases, you do not make a new mergecommit but instead just update to his revision. This will happen frequently on a remote-tracking branch of a remote repository.

fetch

Fetching a branch means to get the branch's head ref from a remote repository, to find out which objects are missing from the local object database, and to get them, too. See also [git-fetch\(1\)](#).

file system

Linus Torvalds originally designed Git to be a user space file system, i.e. the infrastructure to hold files and directories. That ensured the efficiency and speed of Git.

Git archive

Synonym for repository (for arch people).

gitfile

A plain file `.git` at the root of a working tree that points at the directory that is the real repository.

grafts

Grafts enables two otherwise different lines of development to be joined together by recording fake ancestry information for commits. This way you can make Git pretend the set of parents a commit has is different from what was recorded when the commit was created. Configured via the `.git/info/grafts` file.

Note that the grafts mechanism is outdated and can lead to problems transferring objects between repositories; see [git-replace\(1\)](#) for a more flexible and robust system to do the same thing.

hash

In Git's context, synonym for object name.

head

A named reference to the commit at the tip of a branch. Heads are stored in a file in `$GIT_DIR/refs/heads/` directory, except when using packed refs. (See [git-pack-refs\(1\)](#).)

HEAD

The current branch. In more detail: Your working tree is normally derived from the state of the tree referred to by HEAD. HEAD is a reference to one of the heads in your repository, except when using a detached HEAD, in which case it directly references an arbitrary commit.

head ref

A synonym for head.

hook

During the normal execution of several Git commands, call-outs are made to optional scripts that allow a developer to add functionality or checking. Typically, the hooks allow for a command to be pre-verified and potentially aborted, and allow for a post-notification after the operation is done. The hook scripts are found in the `$GIT_DIR/hooks/` directory, and are enabled by simply removing the `.sample` suffix from the filename. In earlier versions of Git you had to make them executable.

index

A collection of files with stat information, whose contents are stored as objects. The index is a stored version of your working tree. Truth be told, it can also contain a second, and even a third version of a working tree, which are used when merging.

index entry

The information regarding a particular file, stored in the index. An index entry can be unmerged, if a merge was started, but not yet finished (i.e. if the index contains multiple versions of that file).

master

The default development branch. Whenever you create a Git repository, a branch named `master` is created, and becomes the active branch. In most cases, this contains the local development, though that is purely by convention and is not required.

merge

As a verb: To bring the contents of another branch (possibly from an external repository) into the current branch. In the case where the merged-in branch is from a different repository,

this is done by first fetching the remote branch and then merging the result into the current branch. This combination of fetch and merge operations is called a pull. Merging is performed by an automatic process that identifies changes made since the branches diverged, and then applies all those changes together. In cases where changes conflict, manual intervention may be required to complete the merge.

As a noun: unless it is a fast-forward, a successful merge results in the creation of a new commit representing the result of the merge, and having as parents the tips of the merged branches. This commit is referred to as a merge commit, or sometimes just a merge.

object

The unit of storage in Git. It is uniquely identified by the SHA-1 of its contents. Consequently, an object can not be changed.

object database

Stores a set of objects, and an individual object is identified by its object name. The objects usually live in `$GIT_DIR/objects/`.

object identifier

Synonym for object name.

object name

The unique identifier of an object. The object name is usually represented by a 40 character hexadecimal string. Also colloquially called SHA-1.

object type

One of the identifiers commit, tree, tag or blob describing the type of an object.

octopus

To merge more than two branches.

origin

The default upstream repository. Most projects have at least one upstream project which they track. By default *origin* is used for that purpose. New upstream updates will be fetched into remote-tracking branches named `origin/name-of-upstream-branch`, which you can see using `git branch -r`.

pack

A set of objects which have been compressed into one file (to save space or to transmit them efficiently).

pack index

The list of identifiers, and other information, of the objects in a pack, to assist in efficiently accessing the contents of a pack.

pathspecc

Pattern used to limit paths in Git commands.

Pathspecs are used on the command line of `git ls-files`, `git ls-tree`, `git add`, `git grep`, `git diff`, `git checkout`, and many other commands to limit the scope of operations to some subset of the tree or worktree. See the documentation of each command for whether paths are relative to the current directory or toplevel. The pathspec syntax is as follows:

- any path matches itself
- the pathspec up to the last slash represents a directory prefix. The scope of that pathspec is limited to that subtree.
- the rest of the pathspec is a pattern for the remainder of the pathname. Paths relative to the directory prefix will be matched against that pattern using `fnmatch(3)` in particular, `*` and `?can` match directory separators.

For example, `Documentation/*.jpg` will match all `.jpg` files in the `Documentation` subtree, including `Documentation/chapter_1/figure_1.jpg`.

A pathspec that begins with a colon `:` has special meaning. In the short form, the leading

colon : is followed by zero or more magic signature letters (which optionally is terminated by another colon :), and the remainder is the pattern to match against the path. The magic signature consists of ASCII symbols that are neither alphanumeric, glob, regex special characters nor colon. The optional colon that terminates the magic signature can be omitted if the pattern begins with a character that does not belong to magic signature symbol set and is not a colon.

In the long form, the leading colon : is followed by a open parenthesis (, a comma-separated list of zero or more magic words, and a close parentheses), and the remainder is the pattern to match against the path.

A pathspec with only a colon means there is no pathspec. This form should not be combined with other pathspec.

top

The magic word top (magic signature: /) makes the pattern match from the root of the working tree, even when you are running the command from inside a subdirectory.

literal

Wildcards in the pattern such as * or ? are treated as literal characters.

icase

Case insensitive match.

glob

Git treats the pattern as a shell glob suitable for consumption by [fnmatch\(3\)](#) with the FNM_PATHNAME flag: wildcards in the pattern will not match a / in the pathname. For example, Documentation/*.html matches Documentation/git.html but not Documentation/ppc/ppc.html or tools/perf/Documentation/perf.html.

Two consecutive asterisks (**) in patterns matched against full pathname may have special meaning:

- A leading ** followed by a slash means match in all directories. For example, **/foo matches file or directory foo anywhere, the same as pattern foo. **/foo/bar matches file or directory bar anywhere that is directly under directory foo.
- A trailing /** matches everything inside. For example, abc/** matches all files inside directory abc, relative to the location of the .gitignore file, with infinite depth.
- A slash followed by two consecutive asterisks then a slash matches zero or more directories. For example, a/**/b matches a/b, a/x/b, a/x/y/b and so on.
- Other consecutive asterisks are considered invalid.

Glob magic is incompatible with literal magic.

exclude

After a path matches any non-exclude pathspec, it will be run through all exclude pathspec (magic signature: !). If it matches, the path is ignored.

parent

A commit object contains a (possibly empty) list of the logical predecessor(s) in the line of development, i.e. its parents.

pickaxe

The term pickaxe refers to an option to the diffcore routines that help select changes that add or delete a given text string. With the --pickaxe-all option, it can be used to view the full changeset that introduced or removed, say, a particular line of text. See [git-diff\(1\)](#).

plumbing

Cute name for core Git.

porcelain

Cute name for programs and program suites depending on core Git, presenting a high level access to core Git. Porcelains expose more of a SCM interface than the plumbing.

pull

Pulling a branch means to fetch it and merge it. See also [git-pull\(1\)](#).

push

Pushing a branch means to get the branch's head ref from a remote repository, find out if it is a direct ancestor to the branch's local head ref, and in that case, putting all objects, which are reachable from the local head ref, and which are missing from the remote repository, into the remote object database, and updating the remote head ref. If the remote head is not an ancestor to the local head, the push fails.

reachable

All of the ancestors of a given commit are said to be reachable from that commit. More generally, one object is reachable from another if we can reach the one from the other by a chain that follows tags to whatever they tag, commits to their parents or trees, and trees to the trees or blobs that they contain.

rebase

To reapply a series of changes from a branch to a different base, and reset the head of that branch to the result.

ref

A name that begins with refs/ (e.g. refs/heads/master) that points to an object name or another ref (the latter is called a symbolic ref). For convenience, a ref can sometimes be abbreviated when used as an argument to a Git command; see [gitrevisions\(7\)](#) for details. Refs are stored in the repository.

The ref namespace is hierarchical. Different subhierarchies are used for different purposes (e.g. the refs/heads/ hierarchy is used to represent local branches).

There are a few special-purpose refs that do not begin with refs/. The most notable example is HEAD.

reflog

A reflog shows the local history of a ref. In other words, it can tell you what the 3rd last revision in *this* repository was, and what was the current state in *this* repository, yesterday 9:14pm. See [git-reflog\(1\)](#) for details.

refspec

A refspec is used by fetch and push to describe the mapping between remote ref and local ref.

remote-tracking branch

A ref that is used to follow changes from another repository. It typically looks like *refs/remotes/foo/bar* (indicating that it tracks a branch named *bar* in a remote named *foo*), and matches the right-hand-side of a configured fetch refspec. A remote-tracking branch should not contain direct modifications or have local commits made to it.

repository

A collection of refs together with an object database containing all objects which are reachable from the refs, possibly accompanied by meta data from one or more porcelains. A repository can share an object database with other repositories via alternates mechanism.

resolve

The action of fixing up manually what a failed automatic merge left behind.

revision

Synonym for commit (the noun).

rewind

To throw away part of the development, i.e. to assign the head to an earlier revision.

SCM

Source code management (tool).

SHA-1

Secure Hash Algorithm 1; a cryptographic hash function. In the context of Git used as a synonym for object name.

shallow repository

A shallow repository has an incomplete history some of whose commits have parents cauterized away (in other words, Git is told to pretend that these commits do not have the parents, even though they are recorded in the commit object). This is sometimes useful when you are interested only in the recent history of a project even though the real history recorded in the upstream is much larger. A shallow repository is created by giving the `--depth` option to [git-clone\(1\)](#), and its history can be later deepened with [git-fetch\(1\)](#).

symref

Symbolic reference: instead of containing the SHA-1 id itself, it is of the format *ref: refs/some/thing* and when referenced, it recursively dereferences to this reference. *HEAD* is a prime example of a symref. Symbolic references are manipulated with the [git-symbolic-ref\(1\)](#) command.

tag

A ref under `refs/tags/` namespace that points to an object of an arbitrary type (typically a tag points to either a tag or a commit object). In contrast to a head, a tag is not updated by the commit command. A Git tag has nothing to do with a Lisp tag (which would be called an object type in Git's context). A tag is most typically used to mark a particular point in the commit ancestry chain.

tag object

An object containing a ref pointing to another object, which can contain a message just like a commit object. It can also contain a (PGP) signature, in which case it is called a signed tag object.

topic branch

A regular Git branch that is used by a developer to identify a conceptual line of development. Since branches are very easy and inexpensive, it is often desirable to have several small branches that each contain very well defined concepts or small incremental yet related changes.

tree

Either a working tree, or a tree object together with the dependent blob and tree objects (i.e. a stored representation of a working tree).

tree object

An object containing a list of file names and modes along with refs to the associated blob and/or tree objects. A tree is equivalent to a directory.

tree-ish (also treeish)

A tree object or an object that can be recursively dereferenced to a tree object. Dereferencing a commit object yields the tree object corresponding to the revisions top directory. The following are all tree-ishes: a commit-ish, a tree object, a tag object that points to a tree object, a tag object that points to a tag object that points to a tree object, etc.

unmerged index

An index which contains unmerged index entries.

unreachable object

An object which is not reachable from a branch, tag, or any other reference.

upstream branch

The default branch that is merged into the branch in question (or the branch in question is rebased onto). It is configured via `branch.<name>.remote` and `branch.<name>.merge`. If the

upstream branch of *A* is *origin/B* sometimes we say *A* is tracking *origin/B*.

working tree

The tree of actual checked out files. The working tree normally contains the contents of the HEAD commit's tree, plus any local changes that you have made but not yet committed.

SEE ALSO

[gittutorial\(7\)](#), [gittutorial-2\(7\)](#), [gitcvs-migration\(7\)](#), [Everyday Git](#)^[1], [The Git User's Manual](#)^[2]

GIT

Part of the [git\(1\)](#) suite.

NOTES

1. Everyday Git
file:///usr/share/doc/git/html/everyday.html
2. The Git User's Manual
file:///usr/share/doc/git/html/user-manual.html