

NAME

bluetoothd - Bluetooth daemon

SYNOPSIS

bluetoothd [--version] | [--help]

bluetoothd [--nodetach] [--compat] [--experimental] [--debug=<files>] [--plugin=<plugins>] [--noplugin=<plugins>]

DESCRIPTION

This manual page documents briefly the **bluetoothd** daemon, which manages all the Bluetooth devices. **bluetoothd** can also provide a number of services via the D-Bus message bus system.

OPTIONS

-v, --version

Print bluetoothd version and exit.

-h, --help

Print bluetoothd options and exit.

-n, --nodetach

Enable logging in foreground. Directs log output to the controlling terminal in addition to syslog.

-d, --debug=<file1>:<file2>:...

Sets how much information bluetoothd sends to the log destination (usually syslog's daemon facility). If the file options are omitted, then debugging information from all the source files are printed. If file options are present, then only debug prints from that source file are printed. The option can be a pattern containing * and ? characters.

Example: --debug=src/adapter.c:src/agent.c

-p, --plugin=<plugin1>,<plugin2>,...

Load these plugins only. The option can be a pattern containing * and ? characters.

-P, --noplugin=<plugin1>,<plugin2>,...

Never load these plugins. The option can be a pattern containing * and ? characters.

-C, --compat

Provide deprecated command line interfaces.

-E, --experimental

Enable experimental interfaces. Those interfaces are not guaranteed to be compatible or present in future releases.

FILES

/etc/bluetooth/main.conf

Location of the global configuration file.

AUTHOR

This manual page was written by Marcel Holtmann, Philipp Matthias Hahn and Fredrik Noring.