

NAME

lsblk - list block devices

SYNOPSIS

lsblk [**options**] [*device...*]

DESCRIPTION

lsblk lists information about all available or the specified block devices. The **lsblk** command reads the **sysfs** filesystem and **udev db** to gather information.

The command prints all block devices (except RAM disks) in a tree-like format by default. Use **lsblk --help** to get a list of all available columns.

The default output, as well as the default output from options like **--fs** and **--topology**, is subject to change. So whenever possible, you should avoid using default outputs in your scripts. Always explicitly define expected columns by using **--output columns-list** in environments where a stable output is required.

Note that **lsblk** might be executed in time when **udev** does not have all information about recently added or modified devices yet. In this case it is recommended to use **udevadm settle** before **lsblk** to synchronize with **udev**.

OPTIONS

-a, --all

Also list empty devices. (By default they are skipped.)

-b, --bytes

Print the SIZE column in bytes rather than in a human-readable format.

-D, --discard

Print information about the discarding capabilities (TRIM, UNMAP) for each device.

-d, --nodeps

Do not print holder devices or slaves. For example, **lsblk --nodeps /dev/sda** prints information about the sda device only.

-e, --exclude list

Exclude the devices specified by the comma-separated *list* of major device numbers. Note that RAM disks (major=1) are excluded by default. The filter is applied to the top-level devices only.

-f, --fs Output info about filesystems. This option is equivalent to **-o NAME,FSTYPE,LABEL,MOUNTPOINT**. The authoritative information about filesystems and raids is provided by the [blkid\(8\)](#) command.

-h, --help

Display help text and exit.

-I, --include list

Include devices specified by the comma-separated *list* of major device numbers. The filter is applied to the top-level devices only.

-i, --ascii

Use ASCII characters for tree formatting.

-l, --list

Produce output in the form of a list.

-m, --perms

Output info about device owner, group and mode. This option is equivalent to **-o NAME,SIZE,OWNER,GROUP,MODE**.

-n, --noheadings

Do not print a header line.

- o, --output *list***
Specify which output columns to print. Use **--help** to get a list of all supported columns.
The default list of columns may be extended if *list* is specified in the format *+list* (e.g. **lsblk -o +UUID**).
- O, --output-all**
Output all available columns.
- P, --pairs**
Produce output in the form of key=value pairs. All potentially unsafe characters are hex-escaped (x<code>).
- p, --paths**
Print full device paths.
- r, --raw**
Produce output in raw format. All potentially unsafe characters are hex-escaped (x<code>) in the NAME, KNAME, LABEL, PARTLABEL and MOUNTPOINT columns.
- S, --scsi**
Output info about SCSI devices only. All partitions, slaves and holder devices are ignored.
- s, --inverse**
Print dependencies in inverse order.
- t, --topology**
Output info about block-device topology. This option is equivalent to **-o NAME,ALIGNMENT,MIN-IO,OPT-IO,PHY-SEC,LOG-SEC,ROTA,SCHED,RQ-SIZE,WSAME**.
- V, --version**
Display version information and exit.
- x, --sort *column***
Sort output lines by output *column*.

NOTES

For partitions, some information (e.g. queue attributes) is inherited from the parent device.

The **lsblk** command needs to be able to look up each block device by major:minor numbers, which is done by using **/sys/dev/block**. This sysfs block directory appeared in kernel 2.6.27 (October 2008). In case of problems with a new enough kernel, check that **CONFIG_SYSFS** was enabled at the time of the kernel build.

AUTHORS

Milan Broz <mbroz@redhat.com>
Karel Zak <kzak@redhat.com>

ENVIRONMENT

Setting **LIBMOUNT_DEBUG=0xffff** enables debug output.

SEE ALSO

[findmnt\(8\)](#), [blkid\(8\)](#), [ls\(1\)](#)

AVAILABILITY

The **lsblk** command is part of the util-linux package and is available from <ftp://ftp.kernel.org/pub/linux/utils/util-linux/>.