

NAME

pam_deny - The locking-out PAM module

SYNOPSIS

pam_deny.so

DESCRIPTION

This module can be used to deny access. It always indicates a failure to the application through the PAM framework. It might be suitable for using for default (the *OTHER*) entries.

OPTIONS

This module does not recognise any options.

MODULE TYPES PROVIDED

All module types (**account**, **auth**, **password** and **session**) are provided.

RETURN VALUES

PAM_AUTH_ERR

This is returned by the account and auth services.

PAM_CRED_ERR

This is returned by the setcred function.

PAM_AUTHTOK_ERR

This is returned by the password service.

PAM_SESSION_ERR

This is returned by the session service.

EXAMPLES

```
##PAM-1.0
#
# If we don't have config entries for a service, the
# OTHER entries are used. To be secure, warn and deny
# access to everything.
other auth required pam_warn.so
other auth required pam_deny.so
other account required pam_warn.so
other account required pam_deny.so
other password required pam_warn.so
other password required pam_deny.so
other session required pam_warn.so
other session required pam_deny.so
```

SEE ALSO

[pam.conf\(5\)](#), [pam.d\(5\)](#), [pam\(7\)](#)

AUTHOR

pam_deny was written by Andrew G. Morgan <morgan@kernel.org>