

NAME

pam_tty_audit - Enable or disable TTY auditing for specified users

SYNOPSIS

pam_tty_audit.so [disable=*patterns*] [enable=*patterns*]

DESCRIPTION

The pam_tty_audit PAM module is used to enable or disable TTY auditing. By default, the kernel does not audit input on any TTY.

OPTIONS**disable=patterns**

For each user matching one of comma-separated glob *patterns*, disable TTY auditing. This overrides any previous **enable** option matching the same user name on the command line.

enable=patterns

For each user matching one of comma-separated glob *patterns*, enable TTY auditing. This overrides any previous **disable** option matching the same user name on the command line.

open_only

Set the TTY audit flag when opening the session, but do not restore it when closing the session. Using this option is necessary for some services that don't **fork()** to run the authenticated session, such as **sudo**.

log_passwd

Log keystrokes when ECHO mode is off but ICANON mode is active. This is the mode in which the tty is placed during password entry. By default, passwords are not logged. This option may not be available on older kernels (3.9?).

MODULE TYPES PROVIDED

Only the **session** type is supported.

RETURN VALUES

PAM_SESSION_ERR

Error reading or modifying the TTY audit flag. See the system log for more details.

PAM_SUCCESS

Success.

NOTES

When TTY auditing is enabled, it is inherited by all processes started by that user. In particular, daemons restarted by an user will still have TTY auditing enabled, and audit TTY input even by other users unless auditing for these users is explicitly disabled. Therefore, it is recommended to use **disable=*** as the first option for most daemons using PAM.

To view the data that was logged by the kernel to audit use the command **aureport --tty**.

EXAMPLES

Audit all administrative actions.

```
session required pam_tty_audit.so disable=* enable=root
```

SEE ALSO

[aureport\(8\)](#), [pam.conf\(5\)](#), [pam.d\(5\)](#), [pam\(8\)](#)

AUTHOR

pam_tty_audit was written by Miloslav Trma <mitr@redhat.com>. The log_passwd option was added by Richard Guy Briggs <rgb@redhat.com>.